

156-30-045-20003

231-30-045-21117

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

(Submit 3 copies to OCD Aztec Office)

Operator MERIDIAN OIL Location: Unit NW Sec. 6 Twp 26 Rng 9

Name of Well/Wells or Pipeline Serviced HUERFANO UNIT #156, #231

cps 907w

Elevation 6506' Completion Date 7/3/75 Total Depth 400' Land Type* N/A

Casing, Sizes, Types & Depths N/A

If Casing is cemented, show amounts & types used N/A

If Cement or Bentonite Plugs have been placed, show depths & amounts used

N/A

Depths & thickness of water zones with description of water when possible:

Fresh, Clear, Salty, Sulphur, Etc. 170'

Depths gas encountered: N/A

Type & amount of coke breeze used: 3100 lbs.

Depths anodes placed: 350', 340', 330', 320', 310', 290', 280', 255', 220', 210'

Depths vent pipes placed: N/A

Vent pipe perforations: 200'

Remarks: qb #1

RECEIVED
MAY 31 1991

OIL CON
DIST

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

WELL CASING
CATHODIC PROTECTION CONSTRUCTION REPORT
DAILY LOG

Log 1140

Drilling Log (Attach Hereto). ☐

Completion Date 7-3-75

Well Name <u>HUCYFANO # 156</u> <u>HUCYFANO # 231</u>		Location <u>NW 6-26N-9W</u>		CPS No. <u>907W</u>	
Type & Size Bit Used <u>6 3/4"</u>		Work Order No. <u>184-54468-19-50-</u> <u>184-55351-19-50-</u>			
Anode Hole Depth <u>400'</u>	Total Drilling Rig Time	Total Lbs. Coke Used <u>3100</u>	Lost Circulation Mat'l Used	No. Sacks Mud Used	
Anode Depth					
# 1 <u>350</u>	# 2 <u>340</u>	# 3 <u>330</u>	# 4 <u>320</u>	# 5 <u>310</u>	# 6 <u>290</u>
# 7 <u>280</u>	# 8 <u>255</u>	# 9 <u>220</u>	# 10 <u>210</u>		
Anode Output (Amps)					
# 1 <u>3.0</u>	# 2 <u>2.6</u>	# 3 <u>3.4</u>	# 4 <u>3.8</u>	# 5 <u>3.6</u>	# 6 <u>2.8</u>
# 7 <u>2.8</u>	# 8 <u>3.2</u>	# 9 <u>3.0</u>	# 10 <u>3.4</u>		
Anode Depth					
# 11	# 12	# 13	# 14	# 15	# 16
# 17	# 18	# 19	# 20		
Anode Output (Amps)					
# 11	# 12	# 13	# 14	# 15	# 16
# 17	# 18	# 19	# 20		
Total Circuit Resistance		No. 8 C.P. Cable Used		No. 2 C.P. Cable Used	
Volts <u>11.8</u>	Amps <u>11.0</u>	Ohms <u>1.07</u>	<u>3205</u>		


Remarks: Driller said water AT 170.
Drilled TO 250', WATER STANDING NEXT
MORNING AT 200' VENT PERFORATED 200'
Logging ANODE STOPPED AT 370

Drilled - 1170.00
Water - 556.36
Imp. - 64.12
Wire - 282.07
Coke - 186.00
Smelter 304.00
Boys - 43.00
Rent - 333.50
Subsidiary 50.00
2705.55

All Construction Completed

Edward R. Paulk
(Signature)

GROUND BED LAYOUT SKETCH



1125

907W

11W	gas/mol
16 C ₁	6.4
30 C ₂	12.2
44 C ₃	10.42
58 IC ₄	12.38
72 IC ₅	13.85
86 IC ₆	15.50
100 IC ₇	17.2
114 C ₈	19.3
128 C ₉	21.64
142 C ₁₀	24.07

MW	MISC	gas/mol
44 CO ₂	0.18	
34 H ₂ S	5.17	
28 N ₂	4.16	
2 H ₂	1.38	

170	1.8	① 50	1.3	Driller said water @ 170
	1.5		1.4	Drilled to 250' static
80	1.8	50	1.0	level @ 200' next morning
	1.4		1.0	vent perforated 200'
90	1.6	70	1.2	bottom
	1.6			
200	1.8			
	1.8			
⑩ 10	1.8			
	1.8			
④ 20	1.8			
	1.2			
30	1.2			
	1.0			
40	1.0	1	350	water 1.0 coke 3.0
	1.2	2	340	1.8 2.6
50	1.4	3	330	2.0 3.4
	1.8	4	320	2.2 3.8
⑧ 60	1.6	5	310	2.2 3.6
	1.4	6	290	1.8 2.8
70	1.4	7	280	1.8 2.8
	1.6	8	255	2.2 3.2
② 80	1.6	9	220	2.0 3.0
	1.6	10	210	2.2 3.4
③ 90	1.6			
	1.4			
300	1.2			
	1.3			
⑤ 10	1.8			
	2.0			
④ 20	1.8			
	1.8			
⑦ 30	1.9			
	1.8			
⑥ 40	1.6			
	1.9			

2905 11.8 11.0 1.07
300
7205

