Form 3160-5 (June 1990)

UNITED STATES

DEPARTMENT OF THE INTERIORS JAN 25 AM 10 43
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

5. Lease Designation and Serial No.

NOO-C-14-20-5579
6. If Indian, Allottee or Tribe Name

## SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT—" for such proposals

Navajo Allotted

7. If Unit or CA, Agreement Designation

SUBMIT IN TRIPLICATE	
I. Type of Well	
Oil Gas Well Other	8. Well Name and No.
2. Name of Operator	Bisti Coal 27 Com #1
Giant Exploration & Production Company	9. API Well No.
3. Address and Telephone No.	
P.O. Box 2810, Farmington, NM 87499 (505)326-3325	10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)	Basin Fruitland Coal
790' FNL, 2510' FEL, Sec 27, T25N, R12W	11. County or Parish, State
$a_{s}=a_{s}$ , $a_{s}=a_{s}$	San Juan, New Mexico
CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPOR	RT, OR OTHER DATA
TYPE OF SUBMISSION TYPE OF ACTION	
Notice of Intent	Change of Plans
Recompletion	New Construction
XX Subsequent Report JANI 9 1993 Plugging Back	Non-Routine Fracturing
Final Abandonment OIL CON. DIV. Casing Repair	Water Shut-Off
Anering Casing	Conversion to Injection
Dist. 3 Exother Drilling progress	Dispose Water
Mark Control of the C	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting	any proposed work. If well is directionally drilled,
give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*	·

Drilled out from under casing with 6-1/4" bit on December 11, 1992. Ran Compensated Density-Neutron logs with caliper and gamma ray. Log tops as follows: Fruitland - 867', Basal Fruitland - 1076', and Pictured Cliffs - 1084'. Ran 27 jts. (1161.95') 4-1/2", 9.5#, J-55, 8rd, ST&C casing. Bakerloked cement nosed guide shoe on bottom and insert flapper float on top of 1st jt. Ran centralizers on top of 1st, 3rd, 5th, 7th, and 9th jts. Casing set at 1158.55', PBD at 1114.95'. Mixed and pumped 65 sks. (133.9 cu.ft.) Class "B" cement containing 2% Thriftyment and 1/4#/sk cellophane flakes. Tailed in with 65 sks. (76.7 cu.ft.) Class "B" cement containing 2% CaCl and 1/4#/sk cellophane flakes. Circulated cement to surface. Pressure tested casing to 3500 psi for 15 min. Waiting on completion.

and 1/4#/sk cellophane tested casing to 3500 p	flakes. Circulated co osi for 15 min. Waitin	ement to surface. ng on completion.	Pressure 2	
			RECEIVE BLM DEC 22 AM FARMINGTO	
14. I hereby certify that the foregoing is true and corre		ring Manager	2 5 DEC 2 1 1992	_
(This space for Federal of State office use)  Approved by Conditions of approval, if any:	TitleNMOCD		ACCEPTED FOR RECORD	
Tid 18 H C C Color 1991 The in the circ	h		IAN 1 4 1993	=

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.