Form 9-881 (Feb. 1951)

		_	
Г			
		-	·
		-	.
		.]	

(SUBMIT IN TRIPLICATE)

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

	•	
Land Office	Santo Pe	
Lease No	077312	,
T1	Weatten	

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	
IOTICE OF INTENTION TO TEST WATER SHUT-OFF	107 TP 112 15 11 W
OTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	
IOTICE OF INTENTION TO SHOOT OR ACIDIZE	1 1
OTICE OF INTENTION TO PULL OR ALTER CASING	I II WAT KAUK
OTICE OF INTENTION TO ABANDON WELL	
(INDICATE ADOLE BY CHECK A	MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)
(INDICATE ABOVE BY CHECK W	FARMINGTON, NEW ME.
• •	April 28 19 60
	, 19 CA
(½ Sec. and Sec. No.) (Twp.)	rom line and ft. from line of sec.
do Ricaco Ficturad Cliffo S	ant or Subdivision) (State or Territory)
(Field) (Cou	inty or Subdivision) (State or Territory)
e elevation of the derrick floor above sea	lavel is SOUT ft
C CICYULION OF THE GOTTON HOOF GOOT OF	· · · · · · · · · · · · · · · · · · ·
DE	TAILS OF WORK
te names of and expected depths to objective sands; sho	w sizes, weights, and lengths of proposed casings; indicate mudding jobs, cemental other important proposed work)
ing points, and	
trainment in 1040 there is endered	and the second s
	", 23%, J.E. casing (113') aut et 123'.
Cemented v/45.9 cm. it. cen	", 23%, J.S. casing (113') set et 123'. ent slurry.
Cenerated v/45.9 cm. ft. cen Cenerat constated of 23 suck	", 23%, J.S. casing (113') set et 123'. ent slurry. s of Ideal Portlend cement, 225 eacks Formix "
Cemented v/45.9 cm. ft. cem Cement consisted of 23 sack To this mixture was added 2	", 23%, J.S. casing (113') set et 123'. ent slurry. s of Ideal Portland coment, 225 sacks Poznix " \$ SA-5.
Cemented v/45.9 cm. ft. cem Cement consisted of 23 sack To this minhure was added 2 Approximate temperature of	", 23%, J.S. casing (113') set et 123'. ent slurry. s of Ideal Portlond cement, 225 eacks Formix " \$ SA-5. cement slurry 50° F.
Cemented v/45.9 cm. ft. cem Cement consisted of 23 sack To this minure was added 2 Approximate temperature of Botimated minimum formation	", 23%, J.S. casing (113') set et 123'. ent slurry. s of Ideal Portland coment, 225 sacks Poznix " \$ SA-5.
Cemented v/45.9 cm. ft. cem Cement consisted of 23 sack To this mixture was added 2 Approximate temperature of Estimated minimal formation Estimate of cement strength	", 23%, J.E. casing (113') set et 123'. ent slurry. s of Ideal Portlead coment, 225 sacks Pozmix " % HA-5. coment slurry 50° F. Vemp. in zone of interest 70° F.
Cemented v/45.9 cm. ft. cem Cement consisted of 23 sack To this mixture was added 2 Approximate temperature of Estimated minimal formation Estimate of cement strength	", 23%, J.S. casing (113') set et 123'. ent slurry. s of Ideal Portland coment, 225 eacks Pormix " % SA-5. coment slurry 50° F. temp. in zone of interest 70° F. ot time of testing 680 FSI.
Cemented v/kJ.9 cm. ft. cem Cement consisted of 23 sack To this mixture was added 2 Approximate temperature of Botimated minimum formation Estimate of coment strength Actual timp cament in place	", 23%, J.S. casing (113') set et 123'. ent slurry. s of Ideal Portland coment, 225 eacks Pormix " % SA-5. coment slurry 50° F. temp. in zone of interest 70° F. ot time of testing 680 FSI.
Cemented v/45.9 cm. ft. cem Cement consisted of 23 sack To this mixture was added 2 Approximate temperature of Estimated minimum formation Estimate of coment strength Actual timp cament in place	". 23%, J.S. casing (113') set et 123'. ent slurry. s of Ideal Portlond coment, 225 eachs Pozmix " \$ 8A-5. coment slurry 50° F. temp. in zone of interest 70° F. ot time of testing 680 FSI. prior to starting casing test - 12 hours.
Cemented v/45.9 cm. ft. cem Cement consisted of 23 sack To this mixture was added 2 Approximate temperature of Estimated minimum formation Estimate of coment strength Actual timp cament in place	", 23%, J.S. casing (113') set et 123'. ent slurry. s of Ideal Portlond cement, 225 accks Pozmix " % SA-5. cement slurry 50° F. temp. in zone of interest 70° F. ot time of testing 680 FSI.
Cemented v/45.9 cm. ft. cem Cement consisted of 23 sack To this minure was added 2 Approximate temperature of Satimated minimal formation Estimate of coment strength Actual time coment in place Reld 500#/30 minutes.	". 236, J.S. casing (113') set et 123'. ent slurry. s of Ideal Portland coment, 225 eachs Pozmix " # MA-5. cement slurry 50° F. temp. in zone of interest 70° F. et time of testing 680 FSI. prior to starting casing test - 12 hours.
Cemented v/45.9 cm. ft. cem Cement consisted of 23 sack To this minure was added 2 Approximate temperature of Satimated minimal formation Estimate of coment strength Actual time coment in place Reld 500#/30 minutes.	", 23%, J.S. casing (113') set et 123'. ent clurry. s of Ideal Portlond coment, 225 eachs Posmix " \$ SA-5. coment clurry 90° F. temp. in zone of interest 70° F. ot time of testing 680 FSI. prior to starting casing test - 12 hours.
Cemented v/45.9 cm. ft. cement confinited of 23 sack to this mixture was added 2 approximate temperature of Setimate of cement formation Estimate of cement strength Actual time cement in place Rela 500%/30 minutes.	". 23%, J.E. casing (113') set et 123'. ent slurry. s of Ideal Portland cement, 225 sacks Pozmix " # HA-5. cement slurry 50° F. temp. in zone of interest 70° F. at time of testing 680 FeI. prior to starting casing test - 12 haurs. All in writing by the Geological Survey before operations may be commenced.
Cemented v/45.9 cm. ft. cem Cement consisted of 23 sack To this minure was added 2 Approximate temperature of Satimated minimal formation Estimate of coment strength Actual time coment in place Reld 500#/30 minutes.	". 23%, J.E. casing (113') set et 123'. ent slurry. s of Ideal Portland cement, 225 eachs Pozmix " # HA-5. cement slurry 50° F. temp. in zone of interest 70° F. at time of testing 680 FeI. prior to starting casing test - 12 haurs. ###################################
Cemented v/45.9 cm. ft. cement consisted of 23 sack to this minture was added 2 approximate temperature of Setimate of committee formation Estimate of coment strength Actual time cament in place Rela 600//30 minutes. understand that this plan of work must receive approximate the plan of work must receive approximate.	". 23%, J.E. casing (113') set et 123'. ent slurry. s of Ideal Portland cement, 225 eachs Pozmix " # HA-5. cement slurry 50° F. temp. in zone of interest 70° F. at time of testing 680 FeI. prior to starting casing test - 12 haurs. ###################################
Cemented v/45.9 cm. ft. cement consisted of 23 sack to this minture was added 2 approximate temperature of Setimate of committee formation Estimate of coment strength Actual time cament in place Rela 600//30 minutes. understand that this plan of work must receive approximate the plan of work must receive approximate.	ent slurry. Sof Ideal Forthcool cement, 225 eacks Formix " HA-5. Cement slurry 50° F. temp. in zone of interest 70° F. at time of testing 580 FSI. prior to starting casing test - 12 hours. RECEIVED All in writing by the Geological Survey before operations may be commerced. BY CON. COM.
Cemented v/45.9 cm. ft. cement consisted of 23 sack To this minture was added 2 approximate temperature of Setimated minimum formation Estimate of coment strength Actual time coment in place Reld 600//30 minutes. understand that this plan of work must receive approximate that this plan of work must receive approximate.	ent slurry. Sof Ideal Portland cement, 225 eacks Poznix " HA-5. Cement slurry 50° F. temp. in zone of interest 70° F. ot time of testing 580 FSI. prior to starting casing test - 12 hours. All in writing by the Geological Survey before operations may be conjugated. ODIC NAI SIGNE. A M. SMITH
Cement consisted of 23 sack To this minure was added 2 approximate temperature of Satissted minimum formation Estimate of coment strength Actual time coment in place Held 500%/30 minutes. understand that this plan of work must receive approve mpany El Paso Natural Gas Compandress Box 997	ent slurry. Sof Ideal Forthcool cement, 225 eacks Formix " HA-5. Cement slurry 50° F. temp. in zone of interest 70° F. at time of testing 580 FSI. prior to starting casing test - 12 hours. RECEIVED All in writing by the Geological Survey before operations may be commerced. BY CON. COM.