

Form 9-331
(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		5. LEASE DESIGNATION AND SERIAL NO. 14-20-603-780
2. NAME OF OPERATOR Pan American Petroleum Corporation		6. IF INDIAN, ALLOTTEE OR TRIBE NAME Navajo Allottee-Eskeenalwood
3. ADDRESS OF OPERATOR Security Life Building, Denver, Colorado 80202		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1925 FSL, 1700 FEL Sec. 25		8. FARM OR LEASE NAME Eskeenalwood "A" Gas Com.
14. PERMIT NO.		9. WELL NO. 1
15. ELEVATIONS (Show whether DF, RT, GR, etc.)		10. FIELD AND POOL, OR WILDCAT Basin Dakota
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA NW/4 SE/4 Sec. 25, T28N, R9W
		12. COUNTY OR PARISH San Juan
		13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other) Supplementary Well History


(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 7-31-65. At a depth of 300' Cemented 10 3/4" 32.75# Casing at 300' with 300 sacks.

Drilled to 2248 and cemented 7 5/8" 24# Casing at 2234 with 600 sacks.

Drilled to TD 6680 and set 4 1/2" Casing at 6680 with stage tool at 4610. Cemented 1st stage with 150 sacks "C" with 6% gel, and 2 lbs tuff plug per sack, followed by 100 sacks "C" Neat. Cemented 2nd stage with 50 sacks "C" Neat and 150 sacks "C" 50-50 pozmix with 4% gel, 1/2 cu. ft. Strata Crete 6 and 1 lb tuff plug per sack followed by 25 sacks "C" Neat cement. Perforated Dakota 6440-6612 and stimulated as indicated on completion report.



18. I hereby certify that the foregoing is true and correct

SIGNED

D. I. Tolleson
D. I. Tolleson

TITLE Administrative Assistant

DATE October 14, 1965

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: