



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office New Mexico
Lease No. 03243
Unit San Juan

RECEIVED

MAY 28 1958

U. S. GEOLOGICAL SURVEY
FARMINGTON, NEW MEXICO

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	<u>Water Frac.</u> <u>X</u>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

May 21, 1958

Well No. 2041 is located 2690 ft. from N line and 200 ft. from E line of sec. 29

SW Sec. 29 28N 5W N.M.P.M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Blanco M.V. Antec. P.O. San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 5975 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

5-9-58. Total Depth 4561'. Plug back T.D. 4530'. Water fractured Point Lookout perforated intervals 4332-32; 4370-50; 4400-4412; 4422-42; 4450-40 with 60,000 gallons water and 60,000% sand. B.D.P. 2000%, max. pr. 1400%, avg. tr. pr. 1400%. I.R. 79 B.P.M. Flush 9200 gallons. Natural gas 181M MCF/D.

5-11-58. Total Depth 4561'. Temporary Bridge Plug at 4292'. Water Fractured Menofee perforated intervals 3941-60; 3993-4010; 4040-68; 4110-4122; 4146-66; 4230-40; 4260-70 with 60,000 gallons water and 60,000% sand. B.D.P. 2000%, max. pr. 3000%, avg. tr. pr. 2800%. I.R. 47 B.P.M. Flush 8100 gallons.

5-11-58. Total Depth 4561'. Temporary Bridge plug at 3930'. Water fractured Pictured Cliffs perforated intervals 2070-80; 2083-2110; with 40,000 gallons water and 40,000% sand. B.D.P. 2700%, max. pr. 2000%, avg. tr. pr. 1400%. I.R. 78 B.P.M. Flush 4300 gallons.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company El Paso Natural Gas Company

Address Box 597
Farmington, New Mexico

By Original Signed D. C. Johnston

Title Petroleum Engineer