

(SUBMIT IN TRIPLICATE)
OFFICE
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
1960 NOV 1 1:30

Land Office Santa Fe
Lease No. 101 09979
Unit Robinson

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	32
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL		

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

U. S. GEOLOGICAL SURVEY
WASHINGTON, NEW MEXICO


Robinson
Well No. 3-D is located 810 ft. from 1N line and 870 ft. from 1E line of sec. 15
October 26, 1960
SW 1/4 Section 15
(1/4 Sec. and Sec. No.) T-26N R-13W N.M.P.M.
Undesignated Dakota San Juan New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 6070 ft. G.L.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Total depth - 6500' P.B.T.D. - 6467'
Ran logs: top of Pictured Cliffs - 1741', Gallup - 5393', Dakota - 6330'
Perforated from 6332-52, 6394-6418, with 4 shots per foot
Ran 205 jts., 6490' of 4 1/2" casing, landed at 6500' with 300 sacks cement
D.V. tool - 1994' with 100 sacks cement
Swabbed hole dry
Tested 2 hours with 500# pressure
Pipe Okay.



I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Astec Oil and Gas Company
Address Drawer # 570
Farmington, New Mexico
By ORIGINAL SIGNED BY JOE C. SALMON
Joe C. Salmon
Title District Superintendent