

6 BLM 1 File
UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER	88 DEC -5 PM 4:20	5. LEASE DESIGNATION AND SERIAL NO. NM-16765
2. NAME OF OPERATOR DUGAN PRODUCTION CORP.	FARMINGTON RESOURCE AREA FARMINGTON, NEW MEXICO	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR P.O. Box 5820, Farmington, NM 87499-5820		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 830' FNL & 1530' FEL		8. FARM OR LEASE NAME Nice
		9. WELL NO. 2
		10. FIELD AND POOL, OR WILDCAT Basin Dakota
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 4, T30N, R14W, NMPM
14. PERMIT NO.	15. ELEVATIONS (Show whether OF, RT, GR, etc.) 5685' GL; 5697' RKB	12. COUNTY OR PARISH San Juan
		13. STATE NM

18. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐
REPAIR WELL ☐	CHANGE PLANS ☐
(Other) ☐	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
(Other) ☒ Spud & Surface Casing	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

DEC 27 1988
FARMINGTON RESOURCE AREA

M.I. & R.U. Four Corners Drilling Company Rig #9.
Spudded a 12 1/4" hole at 4:30 PM 12-3-88. Drilled to 241'. Ran 7 jts. 8-5/8" OD, 24#, 8 Rd, ST&C casing (T.E. 221') set @ 233' RKB. Cemented w/135 sx class "B" + 2% CaCl₂ (total cement slurry = 159 cu.ft.). P.O.B. at 11:30 PM. Circulated 3 bbls cement to surface.

Pressure tested BOP & surface casing 600 psi for 30 minutes - held OK.

RECEIVED
DEC 09 1988

OIL CON. DIV.
DIST. 3

18. I hereby certify that the foregoing is true and correct

SIGNED Jim L. Jacobs
(This space for Federal or State office use)

TITLE Geologist

DATE 12-5-88

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE _____

ACCEPTED FOR RECORD

DEC 06 1988

NMOCC

*See Instructions on Reverse Side

FARMINGTON RESOURCE AREA

BY _____