

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*
(See other instructions on reverse side)

FOR APPROVED
OMB NO. 1004-0137

Expires: December 31, 1991

5. LEASE DESIGNATION AND SERIAL NO.

SF-080379

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

San Juan 29-6 Unit

8. FARM OR LEASE NAME, WELL NO

San Juan 29-6 Unit 13C

9. API WELL NO.

30-039-30385

10. FIELD AND POOL, OR WILDCAT

Blanco Mesaverde

11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA

Surf: Sec.7 T29N R6W, NMPM

BH: Sec.6 T29N R6W, NMPM

RCVD APR 16 '08

OIL CONS DIV

12. COUNTY OR PARISH

Rio Arriba

13. STATE

New Mexico

DIST. 3

19. ELEV. CASINGHEAD

GL 6784' KB 6799'

20. TOTAL DEPTH, MD & TVD

6482' TMD/6134' TVD

21. PLUG, BACK T.D., MD & TVD

6442' TMD/6094' TVD

22. IF MULTIPLE COMPL., HOW MANY*

23. INTERVALS DRILLED BY

ROTARY TOOLS

CABLE TOOLS

Yes

24. PRODUCTION INTERVAL (S) OF THIS COMPLETION-TOP, BOTTOM, NAME (MD AND TVD)*

Blanco Mesaverde 5060' - 6360'

25. WAS DIRECTIONAL SURVEY MADE

Yes

26. TYPE ELECTRIC AND OTHER LOGS RUN

GR/CCL/CBL

27. WAS WELL CORED

No

28. CASING RECORD (Report all strings set in well)

CASING SIZE/GRADE

9 5/8"

WEIGHT, LB./FT.

32.3# H-40

DEPTH SET (MD)

363'

HOLE SIZE

12 1/4"

TOP OF CEMENT, CEMENTING RECORD

surface; 280 sx (354 cf)

AMOUNT PULLED

32 bbls

7"

23# L-80

3783'

8 3/4"

surface; 1031 sx (1811 cf)

64 bbls/ incl plugs

4 1/2"

11.6# L-80

6454'

6 1/4"

TOC 3450'; 289 sx (538 cf)

29. LINER RECORD

SIZE

TOP (MD)

BOTTOM (MD)

SACKS CEMENT*

SCREEN (MD)

SIZE

DEPTH SET (MD)

PACKER SET (MD)

2-3/8"

6296'

30. TUBING RECORD

31. PERFORATION RECORD (Interval, size and number)

.34" @ 1 SPF

PLO/LMF 6122' - 6360' = 30 holes

UMF/CH 5758' - 6094' = 28 holes

Lewis 5060' - 5732' = 30 holes

Total holes = 88

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

6122' - 6360'

Acidize w/10 bbls 15% HCL. Frac 49,350 gals 60%

Slickwater N2 foam w/100,000# 20/40 Brady Sand

5758' - 6094'

Acidize w/10 bbls 15% HCL. Frac 47,588 gals 60%

Slickwater N2 foam w/100,000# 20/40 Brady Sand

N2 = 1,194,800 SCF

5060' - 5732'

Acidize w/10 bbls 15% HCL. Frac w/29,232 gals 20#

Linear 75% N2 foam, w/200,000# 20/40 Brady Sand.

N2 = 1,833,100 SCF

33. PRODUCTION

DATE FIRST PRODUCTION

SI

PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)

Flowing

WELL STATUS (Producing or shut-in)

SI

DATE OF TEST

4/7/08

HOURS TESTED

1

CHOKE SIZE

1/2"

PROD'N FOR TEST PERIOD

0

OIL-BBL

GAS-MCF

WATER-BBL

GAS-OIL RATIO

67 MCF

0

FLOW TUBING PRESS.

CASING PRESSURE

SI -475#

SI -474#

CALCULATED 24-HOUR RATE

0

OIL-BBL

GAS-MCF

WATER-BBL

OIL GRAVITY-API (CORR.)

1597 mcf

0

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc)

To be sold

TEST WITNESSED BY

35. LIST OF ATTACHMENTS

This well is a MV stand alone.

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED

Regulatory Technician

DATE

4/14/08

*(See Instructions and Spaces for Additional Data on Reverse Side)

APR 15 2008

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department of agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCD

FARMINGTON FIELD OFFICE

Well Name		San Juan 29-6 Unit 13C			
Ojo Alamo	2920'	3200'	White, cr-gr ss.	Ojo Alamo	2920'
Kirtland	3200'	3584'	Gry sh interbedded w/tight, gry, fine-gr ss.	Kirtland	3200'
Fruitland	3584'	4024'	Dk gry-gry carb sh, coal, grn silts, light-med gry, tight, fine gr ss	Fruitland	3584'
Pictured Cliffs	4024'	4187'	Bn-Gry, fine grn, tight ss.	Pic.Cliffs	4024'
Lewis	4187'	4567'	Shale w/siltstone stringers	Lewis	4187'
Huerfanito Bentonite	4567'	5050'	White, waxy chalky bentonite	Huerfanito Bent.	4567'
Chacra	5050'	5752'	Gry fn grn silty, glauconitic sd stone w/drck gry shale	Chacra	5050'
Mesa Verde	5752'	5895'	Light gry, med-fine gr ss, carb sh & coal	Mesa Verde	5752'
Menefee	5895'	6278'	Med-dark gry, fine gr ss, carb sh & coal	Menefee	5895'
Point Lookout	6278'		Med-light gry, very fine gr ss w/frequent sh breaks in lower part of formation	Point Lookout	6278'

WELL 29-6

WELL 29-6