

92 - 30-039-07600

129 30-039-23749

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS  
NORTHWESTERN NEW MEXICO  
(Submit 3 copies to OCD Aztec Office)

Operator MERIDIAN OIL Location: Unit SW Sec. 16 Twp 29 Rng 7

Name of Well/Wells or Pipeline Serviced SAN JUAN 29-7 UNIT #92, #129

cps 292w

Elevation 6338' Completion Date 6/8/70 Total Depth 700' Land Type\* N/A

Casing, Sizes, Types & Depths N/A

If Casing is cemented, show amounts & types used N/A

If Cement or Bentonite Plugs have been placed, show depths & amounts used  
N/A

Depths & thickness of water zones with description of water when possible:

Fresh, Clear, Salty, Sulphur, Etc. 340'

**RECEIVED**

MAY 31 1991

Depths gas encountered: N/A

Type & amount of coke breeze used: 100 SACKS

**OIL CON. DIV**  
**DIST. 3**

Depths anodes placed: 670', 660', 650', 625', 615', 525', 440', 430', 375', 365'

Depths vent pipes placed: N/A

Vent pipe perforations: N/A

Remarks: gb #2 ANODE #3 & #6 SINGLE . ALL OTHERS TANDEM.

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

\*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.  
If Federal or Indian, add Lease Number.

## CATHODIC PROTECTION CONSTRUCTION REPORT

DAILY LOG

Drilling Log (Attach Hereto). ☐Completion Date 6/8/70

|                                            |                         |                                 |                             |                                          |                |
|--------------------------------------------|-------------------------|---------------------------------|-----------------------------|------------------------------------------|----------------|
| Well Name<br><b>S.J. 29-7 # 92</b>         |                         | Location<br><b>SW 16-29N 7W</b> |                             | CPS No.<br><b>292 W</b>                  |                |
| Type & Size Bit Used<br><b>6 3/4" ROCK</b> |                         |                                 |                             | Work Order No.<br><b>184-40065-50-20</b> |                |
| Anode Hole Depth<br><b>700'</b>            | Total Drilling Rig Time | Total Lbs. Coke Used            | Lost Circulation Mat'l Used | No. Sacks Mud Used                       |                |
| Anode Depth                                |                         |                                 |                             |                                          |                |
| #1 <b>670'</b>                             | #2 <b>660'</b>          | #3 <b>650'</b>                  | #4 <b>625'</b>              | #5 <b>615'</b>                           | #6 <b>525'</b> |
| #7 <b>440'</b>                             | #8 <b>430'</b>          | #9 <b>375'</b>                  | #10 <b>365'</b>             |                                          |                |
| Anode Output (Amps)                        |                         |                                 |                             |                                          |                |
| #1 <b>3.0</b>                              | #2 <b>3.0</b>           | #3 <b>2.2</b>                   | #4 <b>3.5</b>               | #5 <b>3.5</b>                            | #6 <b>2.7</b>  |
| #7 <b>4.0</b>                              | #8 <b>4.0</b>           | #9 <b>5.5</b>                   | #10 <b>5.5</b>              |                                          |                |
| Anode Depth                                |                         |                                 |                             |                                          |                |
| #11                                        | #12                     | #13                             | #14                         | #15                                      | #16            |
| #17                                        | #18                     | #19                             | #20                         |                                          |                |
| Anode Output (Amps)                        |                         |                                 |                             |                                          |                |
| #11                                        | #12                     | #13                             | #14                         | #15                                      | #16            |
| #17                                        | #18                     | #19                             | #20                         |                                          |                |
| Total Circuit Resistance                   |                         |                                 | No. 8 C.P. Cable Used       |                                          |                |
| Volts <b>11.0</b>                          |                         |                                 | Amps <b>15.0</b>            |                                          |                |
| Ohms <b>0.73</b>                           |                         |                                 | No. 2 C.P. Cable Used       |                                          |                |

Remarks: Installed By C.P.S. (Contract)Paired Anodes = #1 & 2, #4 & 5, #7 & 8, 9 & 10.Single Anodes = #3 & #6Found WATER AT 340' Drilled with Air TO 380'Pumped 60 SACKS TO ABOVE TOP ANODESComplete COKING Hole NEXT Day By Slurry 100 SACKS TO  
ANODES #1 & 2 Responded 200MA TO COTE

All Construction Completed

Placed copy in RectifierB. R. Parker  
(Signature)

GROUND BED LAYOUT SKETCH

