

92 - 30-039-07600
129 30039-23749

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 copies to OCD Aztec Office)

Operator MERIDIAN OIL Location: Unit SW Sec. 16 Twp 29 Rng 7

Name of Well/Wells or Pipeline Serviced SAN JUAN 29-7 UNIT #92, #129
cps 292w

Elevation 6338 Completion Date 6/8/70 Total Depth 700' Land Type* N/A

Casing, Sizes, Types & Depths N/A

If Casing is cemented, show amounts & types used N/A

If Cement or Bentonite Plugs have been placed, show depths & amounts used
N/A

Depths & thickness of water zones with description of water when possible:
Fresh, Clear, Salty, Sulphur, Etc. 340'

RECEIVED

MAY 31 1991

Depths gas encountered: N/A

Type & amount of coke breeze used: 100 SACKS

OIL CON. DIV
DIST. 3

Depths anodes placed: 670', 660', 650', 625', 615', 525', 440', 430', 375', 365'

Depths vent pipes placed: N/A

Vent pipe perforations: N/A

Remarks: gb #2 ANODE #3 & #6 SINGLE . ALL OTHERS TANDEM.

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

CATHODIC PROTECTION CONSTRUCTION REPORT

DAILY LOG

Drilling Log (Attach Hereto). ☐Completion Date 6/8/70

Well Name S.J. 29-7 # 92		Location SW 16-29N 7W		CPS No. 292 W	
Type & Size Bit Used 6 3/4" ROCK				Work Order No. 184-40065-50-20	
Anode Hole Depth 700'	Total Drilling Rig Time	Total Lbs. Coke Used	Lost Circulation Mat'l Used	No. Sacks Mud Used	
Anode Depth					
# 1 670'	# 2 660'	# 3 650'	# 4 625'	# 5 615'	# 6 525'
# 7 440'	# 8 430'	# 9 375'	# 10 365'		
Anode Output (Amps)					
# 1 3.0	# 2 3.0	# 3 2.2	# 4 3.5	# 5 3.5	# 6 2.7
# 7 4.0	# 8 4.0	# 9 5.5	# 10 5.5		
Anode Depth					
# 11	# 12	# 13	# 14	# 15	# 16
# 17	# 18	# 19	# 20		
Anode Output (Amps)					
# 11	# 12	# 13	# 14	# 15	# 16
# 17	# 18	# 19	# 20		
Total Circuit Resistance			No. 8 C.P. Cable Used		
Volts 11.0			Amps 15.0		
Ohms 0.73			No. 2 C.P. Cable Used		

Remarks: Installed By C.P.S. (Contract)Paired Anodes = #1 & 2, #4 & 6, #7 & 8, 9 & 10.Single Anodes = #3 & #6Found WATER AT 340' Drilled with Air TO 380'Pumped 60 Sacks TO Above Top AnodesComplete Coking Hole Next Day By Slurry 100 Sacks TO
Anodes #1 & 2 Responded 200MA TO COKE

All Construction Completed

Placed copy in RectifierB. R. Parker
(Signature)

GROUND BED LAYOUT SKETCH

