

10-30-039-07741
447-30-039-24634

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 copies to OCD Aztec Office)

Operator MERIDIAN OIL Location: Unit NE Sec 31 Twp 30 Rng 7

Name of Well/Wells or Pipeline Serviced SAN JUAN 30-6 UNIT #10, #447

cps 260w

Elevation 6227' Completion Date 7/24/69 Total Depth 600' Land Type* N/A

Casing, Sizes, Types & Depths N/A

If Casing is cemented, show amounts & types used N/A

If Cement or Bentonite Plugs have been placed, show depths & amounts used
N/A

Depths & thickness of water zones with description of water when possible:
Fresh, Clear, Salty, Sulphur, Etc. 310'

Depths gas encountered: N/A

Type & amount of coke breeze used: 0 lbs.

Depths anodes placed: NONE

Depths vent pipes placed: 0'

Vent pipe perforations: 0'

Remarks: qb #2 HOLE #2 TWIST OFF DRILL PIPE - COULD NOT RECOVER. ABANDONED.

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

RECEIVED

MAY 31 1991

OIL CON. DIV.
DIST. 3

WELL CASING
CATHODIC PROTECTION CONSTRUCTION REPORT
DAILY LOG

5 1/8 #200 = 160 ✓

4 1/2" Rock 41829 = 400 ✓

Drilling Log (Attach Hereto). ☐

Completion Date 7-24-69

Well Name <u>31-30-7 #10</u>		Location <u>N=31-30-7</u>		CPS No. <u>260 W</u>	
Type & Size Bit Used <u>7 1/8" IN 610 = 360 - 3 1/2" 74 = 200 - 7 1/8" 86 = 40</u>				Work Order No. <u>184-40024-50-20</u>	
Anode Hole Depth <u>600</u>	Total Drilling Rig Time <u>48 Hrs</u>	Total Lbs. Coke Used <u>0</u>	Lost Circulation Mat'l Used <u>0</u>	No. Sacks Mud Used <u>13</u>	
Anode Depth					
# 1	# 2	# 3	# 4	# 5	# 6
Anode Output (Amps)					
# 1	# 2	# 3	# 4	# 5	# 6
Anode Depth					
# 11	# 12	# 13	# 14	# 15	# 16
Anode Output (Amps)					
# 11	# 12	# 13	# 14	# 15	# 16
Total Circuit Resistance			No. 8 C.P. Cable Used		
Volts	Amps	Ohms	No. 2 C.P. Cable Used		

Remarks:

Twist off Drill Pipe - Could Not
Recover - Abandoned Hole -

All Construction Completed

Amels

(Signature)

GROUND BED LAYOUT SKETCH

Sheet 2 of 3

N

LEASER

WELL NO. 3000

CONTRACT TO

MORNING

DAYLIGHT

REPORT NO.

DATE _____
PAGE _____

13

[illegible]

STARS

王公大臣

REMARKS

7-20-69 left at 6:00 am moved from old bar to new loc. Drilled from 0' to 210' leaving 4100
7-21-69 left at 6 am moved to 2nd bar moved in hole drilled from 210' to 560' with 41's & came on & had gas on
7-22-69 drilled from 0' to 210' leaving 5100 pm
7-23-69 left at 6 am moved to 3rd bar moved in hole drilled 160' worked on rig from 8:30 am to 10:30 am drilled
from 140' to 360' leaving 5100 pm
7-23-69 left at 6 am moved to 4th bar moved from 140' to 360' drilled from 360' to 560' leaving 5100 pm
7-24-69 left at 6 am moved to 5th bar moved from 360' to 560' drilled from 560' to 600' drilled off hole at 6:00 PM from 6:00 PM to 6:00 PM
7-25-69 left at 6 am moved to 6th bar moved from 560' to 600' drilled off hole at 6:00 PM from 6:00 PM to 6:00 PM

SIGNED: Toipushen

Company Supervisor

David