

10 - 30-039-07741
447- 30-039- 24634

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 copies to OCD Aztec Office)

Operator MERIDIAN OIL Location: Unit NE Sec. 31 Twp 30 Rng 7

Name of Well/Wells or Pipeline Serviced SAN JUAN 30-6 UNIT #10, #447

cps 260w

Elevation 6227' Completion Date 8/23/69 Total Depth 500' Land Type* N/A

Casing, Sizes, Types & Depths N/A

If Casing is cemented, show amounts & types used N/A

If Cement or Bentonite Plugs have been placed, show depths & amounts used
N/A

Depths & thickness of water zones with description of water when possible:

Fresh, Clear, Salty, Sulphur, Etc. N/A

Depths gas encountered: N/A

Type & amount of coke breeze used: 9000 lbs.

Depths anodes placed: 454', 448', 399', 350', 344', 284', 278', 272', 258'


Depths vent pipes placed: 448' OF 3/4" HOSE

Vent pipe perforations: 448'

Remarks: gb #2 HOEL #3 PLASTIC MOLD USED TO CAP ANODES-DID NOT USE SHRINK SLEEVE.

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.



WELL CASING
CATHODIC PROTECTION CONSTRUCTION REPORT
DAILY LOG

5' - 205 = 85
5' - 2279 = 310 ✓

Drilling Log (Attach Hereto). ☐

Completion Date 2-23-69

Well Name <u>SN 30-6 # 10</u>		Location <u>N 31-30-7</u>		CPS No. <u>260 W</u>	
Type & Size Bit Used <u>7 1/2 SB 972=440 W 761=60</u>		Work Order No. <u>181-40024-50-20</u>			
Anode Hole Depth <u>500</u>	Total Drilling Rig Time <u>35 min</u>	Total Lbs. Coke Used <u>9000</u>	Lost Circulation Mat'l Used <u>0</u>	No. Sacks Mud Used <u>2</u>	
Anode Depth	# 1 <u>454</u>	# 2 <u>448</u>	# 3 <u>399</u>	# 4 <u>350</u>	# 5 <u>344</u>
	# 6 <u>284</u>	# 7 <u>278</u>	# 8 <u>272</u>	# 9 <u>258</u>	# 10
Anode Output (Amps)	# 1 <u>2.0</u>	# 2 <u>2.0</u>	# 3 <u>2.3</u>	# 4 <u>2.5</u>	# 5 <u>2.4</u>
	# 6 <u>2.8</u>	# 7 <u>3.2</u>	# 8 <u>3.7</u>	# 9 <u>4.0</u>	# 10
Anode Depth	# 11	# 12	# 13	# 14	# 15
	# 16	# 17	# 18	# 19	# 20
Anode Output (Amps)	# 11	# 12	# 13	# 14	# 15
	# 16	# 17	# 18	# 19	# 20
Total Circuit Resistance	Volts <u>12.7</u>		Amps <u>9.5</u>	Ohms <u>1.33</u>	No. 8 C.P. Cable Used <u>3534</u>
					No. 2 C.P. Cable Used <u>3267 in. Anodes 267-Surface D</u>

Remarks: 3/4" Hose to No. 2 Anode; Perforated - 11
Did Not use Borafos

Plastic Mold used to Cap Anodes - Did Not use
Shrink sleeve

All Construction Completed

[Signature]
(Signature)

Note -
Sheet 30F3

No. 2 Ground Bed

GROUND BED LAYOUT SKETCH

207

Contractor making
road for hole test

No. 1 Ground Bed

