

30-039-07842
30-039-24380

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 copies to OCD Aztec Office)

Operator MERIDIAN OIL Location: Unit H Sec. 13 Twp. 30 Rng. 7

Name of Well/Wells or Pipeline Serviced SAN JUAN 30-6 UNIT #71, #463

cps 155w

Elevation 6420' Completion Date 7/11/69 Total Depth 560' Land Type* N/A

Casing, Sizes, Types & Depths N/A

If Casing is cemented, show amounts & types used N/A

If Cement or Bentonite Plugs have been placed, show depths & amounts used
N/A

Depths & thickness of water zones with description of water when possible:

Fresh, Clear, Salty, Sulphur, Etc. 50' & 70'

RECEIVED

MAY 31 1991

Depths gas encountered: N/A

OIL CON. DIV
DIST. 3

Type & amount of coke breeze used: 9375 lbs.

Depths anodes placed: 522', 492', 477', 471', 465', 340', 334', 328', 322'

Depths vent pipes placed: 477' OF 3/4" HOSE

Vent pipe perforations: 340'

Remarks: sqb #2

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

5 1/8" insert #115 = 200'
5" Rock = 75662 = 300
5" Rock 75665 = 100

Drilling Log (Attach Hereto).

Completion Date 7-11-69

Well Name 5J 30-6 #71				Location 13-30-7				CPS No. 155W			
Type & Size Bit Used 7 7/8-797303=320 173096=180								Work Order No. 184-52668-50-20			
Anode Hole Depth 560		Total Drilling Rig Time 67 1/2 Hrs		Total Lbs. Coke Used 9375		Lost Circulation Mat'l Used 1		No. Sacks Mud Used 7			
Anode Depth											
# 1 522	# 2 492	# 3 477	# 4 471	# 5 465	# 6 340	# 7 334	# 8 328	# 9 322	# 10		
Anode Output (Amps)											
# 1 2.0	# 2 2.0	# 3 2.4	# 4 2.4	# 5 2.4	# 6 3.9	# 7 4.4	# 8 3.8	# 9 2.8	# 10		
Anode Depth											
# 11	# 12	# 13	# 14	# 15	# 16	# 17	# 18	# 19	# 20		
Anode Output (Amps)											
# 11	# 12	# 13	# 14	# 15	# 16	# 17	# 18	# 19	# 20		
Total Circuit Resistance				No. 8 C.P. Cable Used				No. 2 C.P. Cable Used			
Volts 13.6		Amps 10.6		Ohms 1.28		4111		0			

Remarks: 3/4" Hose to No 3 Anode Perforated 340'
50 lbs Barafos used

Plastic mold used on All Anodes - Did Not use shrink sleeve (shrink sleeve on no. 9 Anode only)

All Construction Completed

Parrels
(Signature)

(Signature)

GROUND BED LAYOUT SKETCH



