

30-045-08973

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 copies to OCD Aztec Office)

Operator Texaco E&P Inc. Location: Unit K Sec. 36 Twp 30N Rng 10W

Name of Well/Wells or Pipeline Serviced New Mexico "C" #1

Elevation _____ Completion Date 5/18/71 Total Depth 300' Land Type* _____

Casing, Sizes, Types & Depths 6 3/4" hole to 300'

If Casing is cemented, show amounts & types used Unknown

If Cement or Bentonite Plugs have been placed, show depths & amounts used
Unknown

Depths & thickness of water zones with description of water when possible:
Fresh, Clear, Salty, Sulphur, Etc. See attached log

Depths gas encountered: _____

Type & amount of coke breeze used: _____

Depths anodes placed: See attached log

Depths vent pipes placed: _____

Vent pipe perforations: _____

Remarks: _____

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

WELL TYPE GROUNDBED DATA

DATA SHEET NO. 1

COMPANY TEXACO INC. JOB No. 6142 DATE: 5-18-81
 WELL: NEW MEX COM "C" WELL No. 1 PIPELINE: _____
 LOCATION: SEC. 36 TWP. 30N RGE. 10W CO. SAN JUAN STATE NEW MEX
 ELEV. _____ FT: ROTARY 300 FT: CABLE TOOL _____ FT: CASING _____ FT.
 GROUNDBED: DEPTH 300 FT. DIA. 1 3/4 IN. GAS 5100 LBS. ANODES 10 1 1/2 X 60 C D-51

DEPTH, FT.	DRILLER'S LOG	DRILL PIPE TO STRUCTURE			EXPLORING ANODE TO STRUCTURE			DEPTH, TOP OF ANODES
		E	I	R	E	I	R	
0-5	SAND							
5-10								
10-15								
15-20								
20-25								
25-30								
30-35								
35-40								
40-45								
45-50								
50-55	BROWN SHALE				12	1.6		
55-60						2.0		
60-65						2.2		
65-70						2.4		
70-75						2.0		
75-80						1.6		
80-85	SAND (wet)					1.4		
85-90						1.3		
90-95						1.2		
95-100						1.1		
100-105						1.2		
105-110	BENTONITE SAND					1.2		
110-115						1.1		
115-120						.9		
120-125						1.0		
125-130						1.1		
130-135						1.4		
135-140						2.0		
140-145						2.0		
145-150						2.0		
150-155						2.2		✓ 150
155-160						1.9		
160-165						1.6		
165-170						1.4		
170-175	BLUE SHALE					1.7		
175-180						2.0		✓ 175
180-185						1.8		
185-190						2.2		✓ 185
190-195						2.0		
195-200						2.0		✓ 195
200-205						1.9		
205-210						1.9		✓ 205
210-215						2.0		

GROUNDBED RESISTANCE: (1) VOLTS _____ + AMPS _____ = _____ OHMS

(2) VIBROGROUND _____ OHMS



cathodic protection service

HOUSTON TEXAS

DATA SHEET NO. 2

[illegible]

GROUNDING RESISTANCE: (1) VOLTS 12 + AMPS 2.2 = _____ OHMS

(2) VIDEOGROUND _____ CHMS



cathodic protection service

HOUSTON TEXAS