

30-045-09568

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 copies to OCD Aztec Office)

Operator Texaco E&P Inc. Location: Unit B Sec. 13 Twp 30N Rng 12W

Name of Well/Wells or Pipeline Serviced M.L.R. Wright #1B

Elevation _____ Completion Date 12/16/81 Total Depth 302' Land Type* _____

Casing, Sizes, Types & Depths 7" Casing from surface to 87'
6" hole to T.D.

If Casing is cemented, show amounts & types used Unknown

If Cement or Bentonite Plugs have been placed, show depths & amounts used
Unknown

Depths & thickness of water zones with description of water when possible:
Fresh, Clear, Salty, Sulphur, Etc. See attached log

Depths gas encountered: _____

Type & amount of coke breeze used: _____

Depths anodes placed: See attached log

Depths vent pipes placed: _____

Vent pipe perforations: _____

Remarks: _____

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

WELL TYPE GROUND BED DATA

DATA SHEET NO. 1 OF 1

COMPANY GETTY OIL COMPANY JOB No. 10678 DATE: 12-16-81
WELL: M.L.R. WRIGHT GAS UNIT #1 PIPELINE: _____
LOCATION: SEC. 13 TWP. 30N RGE. 12W CO. SAN JUAN STATE NEW MEXICO
ELEV. _____ FT: ROTARY 208 FT: CABLE TOOL 92 FT: CASING 87 7" FT.
GROUNDBED: DEPTH 302 FT. DIA. 6" IN. GAS 3800 LBS. ANODES 10-CD-DS1

DEPTH, FT.	DRILLER'S LOG	EXPLORING ANODE TO STRUCTURE			NO COKE	WITH COKE	DEPTH TOP OF ANODES	
		E	I	R	R	R	NO.	FT.
90		11.58	1.24					
			1.85					
100			1.80					
			1.63					
10			1.34					
			1.80					
20			2.13					
			2.24					
30			2.28					
			2.00					
40			2.34					
			2.32					
50			3.64					
			5.06					
60			3.91		4.30	5.40	10	160'
			3.33					
70			4.53					
			4.30		4.04	5.25	9	175'
80			3.67					
			4.10		3.72	5.05	8	185'
90			4.30					
			4.32		4.07	5.71	7	195'
200			4.52					
			4.25		4.17	5.55	6	205'
10			3.74					
			3.40		3.28	4.60	5	215'
20			3.23					
			3.12		3.15	4.40	4	225'
30			2.81					
			3.41					
40			3.45		3.62	4.68	3	240'
			3.01					
50			3.01					
			3.18		3.00	4.20	2	255'
60			3.07					
			2.83					
70			2.89					
			3.05					
80			3.20		3.19	4.51	1	280'
			3.31					
90			3.18					
			2.69					
300	T.D. 302		2.66					

GROUNDBED RESISTANCE: (1) VOLTS 11.58 + AMPS 21.5 = .54 OHMS

(2) VIBROGROUND _____ OHMS