DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS NORTHWESTERN NEW MEXICO (Submit 3 copies to OCD Aztec Office)

Operator UNOCAL, Oil & Gas Division Location: Unit F Sec. 19 Twp 27N Rng 6W
Name of Well/Wells or Pipeline Serviced Rincon Unit #174M, Rincon Unit #109
Elevation 6520 GR Completion Date 11-19-92 Total Depth 300' Land Type* F
Casing, Sizes, Types & Depths NONE
If Casing is cemented, show amounts & types used NONE
If Cement or Bentonite Plugs have been placed, show depths & amounts used
750 lbs. Enviro plug coarse chips (0' - 50')
Depths & thickness of water zones with description of water when possible: Fresh, Clear, Salty, Sulphur, Etc. 100' to 105', 5' thick (moist)
Saity, Suiphur, Ltc. 100 to 100 ; 5 three (morse)
Depths gas encountered: NONE
Type & amount of coke breeze used: 2500 lbs. SWB Petroleum Coke
Depths anodes placed: 130', 135', 140', 145', 150', 155', 160', 165', 170', 175'
Depths anodes placed: 130', 135', 140', 145', 150', 155', 160', 165', 170', 175' Depths vent pipes placed: 0' to 300' Vent pipe perforations: 1/8" diameter holes, 120' to 300'
Depths vent pipes placed: 0' to 300'

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee. If Federal or Indian, add Lease Number.

