

30-045-07414

CPS GROUND BED CONSTRUCTION WORKSHEET

CP# 2563-W		P/L NAME(S), NUMBER(S) KUTZ CANYON O+G #1									
WO # M652	TOTAL	VOLTS 12.22	AMPS 38.4	- OHMS 318	DATE 9/8/93	NAME: JOHN L. MOSS					
REMARKS (notes for construction log) Driller Reported A Damp Zone AT 65' AND WATER AT 295'. A WATER SAMPLE WAS TAKEN. INSTALLED 388' OF 1" PE VENT PIPE, WITH THE BOTTOM 260' PERFORATED. COKE BREEZE TO 100'.											
DEPTH	LOG ANODE	ANODE *	DEPTH	LOG ANODE	ANODE *	DEPTH	LOG ANODE	ANODE *	DEPTH	LOG ANODE	ANODE *
100	2.0		295	3.4		490			685		
105	1.6		300	4.5	7	495			690		
110	1.7		305	4.3		500			695		
115	1.9		310	4.0	6	505			700		
120	1.4		315	4.4		510			ANODE	DEPTH	NO.
125	1.4		320	4.4	5	515			*	COKE	FULLY
130	1.5		325	4.4		520			1	370'	4.3
135	1.5		330	4.4	4	525			2	360'	4.5
140	1.8		335	4.4		530			3	341'	4.3
145	3.6		340	4.6	3	535			4	330'	4.7
150	4.4	15	345	4.1		540			5	320'	4.8
155	3.7		350	3.4		545			6	310'	4.5
160	3.5		355	4.0		550			7	300'	4.9
165	3.1		360	4.2	2	555			8	260'	4.5
170	3.1		365	4.0		560			9	250'	4.0
175	3.9	14	370	4.1	1	565			10	240'	4.0
180	4.0		375	4.3		570			11	205'	4.2
185	4.3	13	380	4.1		575			12	195'	4.1
190	4.2		385			580			13	185'	4.8
195	3.8	12	390	T.D.	388'	585			14	175'	4.1
200	3.4		395			590			15	150'	4.7
205	3.8	11	400			595			16		
210	3.8		405			600			17		
215	3.5		410			605			18		
220	2.9		415			610			19		
225	2.9		420			615			20		
230	2.6		425			620			21		
235	3.1		430			625			22		
240	3.7	10	435			630			23		
245	3.8		440			635			24		
250	3.7	9	445			640			25		
255	4.0		450			645			26		
260	4.1	8	455			650			27		
265	3.4		460			655			28		
270	2.7		465			660			29		
275	3.0		470			665			30		
280	3.1		475			670					
285	2.7		480			675					
290	2.6		485			680					

RECEIVED
JAN 31 1994
OIL CON. DIV.
DIST. 3

DISTRIBUTION - original - permanent CPS FILE

T.D. 388'

copy - Division Corrosion Supervisor
copy - Region Corrosion Specialist