

30-045-23890

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 copies to OCD Aztec Office)

Operator LADD PETROLEUM CORPORATION Location: Unit P Sec 26 Twp 30N Rng 13W

Name of Well/Wells or Pipeline Served FEDERAL A3E

Elevation _____ Completion Date 11-23-87 Total Depth 250 Land Type* _____

Casing, Sizes, Types & Depths NONE

If Casing is cemented, show amounts & types used NONE

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NONE

Depths & thickness of water zones with description of water when possible:

Fresh, Clear, Salty, Sulphur, Etc. FIRST WATER AT 80', STAMMER

Depths gas encountered: NONE

Type & amount of coke breeze used: 99.9% CARBON CARBON - 812.5#

Depths anodes placed: 5 FROM 125' TO 165'

Depths vent pipes placed: 0' TO 250'

Vent pipe perforations: 115' TO 250'

Remarks: _____

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Federal
If Federal or Indian, add Lease Number.

RECEIVED
FEB 04 1991
OIL CON. DIV.
DIST. 3

GENERAL

CATHODIC PROTECTION SERVICES
WELL TYPE GROUNDED DATA

DATA SHEET NO. 1061

COMPANY LAHO PETROLEUM PIPELINE: JOB NO. 13123 DATE: 11-23-87

WELL: EDDERH #1 #3 E

LOCATION: SEC 26 TWP. 30N RGE. 13W CO. SAS SAIN STATE WY

ELEV. FT: ROTARY 250 FT: CABLE TOOL 0 FT: CASING 0

GROUNDED, DEPTH 250 FT. DIA. 6 1/2 IN. GAS 8125 LBS. ANODES 5 L108 STRIKE

DEPTH, FT.	DRILLER'S LOG	EXPLORING ANODE TO STRUCTURE			NO COKE	WITH COKE	DEPTH OF ANODES	FT.
		E	I	R				
100	FIRST WATER AT 80'							
5	SAND		0.4					
10			0.4					
15			0.6					
20			0.4					
25			0.4					
30			0.8					135
35	SANDY SHALE		1.3					
40			1.5					
45			1.6		2.7	6.8		
50			6.6					
55	SAND		0.6					
60			0.6					
65			0.5					145
70			0.3					
75			0.5					
80			0.4					
85			0.6					
90			0.5					
95			0.5					
100			0.3					
15			0.3					
20			0.3					
25			0.3					
30			0.2					
35			0.3					
40			0.4					
45			0.3					
50			0.2					
55								
60								
65								
70								
75								
80								
85								
90								
95								
100								

GROUNDED RESISTANCE (I) VOLTS 12.4 - AMPS 6.8 - 1.82 OHMS

(2) VIBROGROUND 1.82 OHMS