

30-045-2680

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 copies to OCD Aztec Office)

Operator LADD PETROLEUM CORPORATION Location: Unit P Sec. 13 Twp. 27N Rng. 10W

Name of Well/Wells or Pipeline Serviced KWAUFF AIE

Elevation _____ Completion Date 1-5-88 Total Depth 300 Land Type*

Casing, Sizes, Types & Depths NONE

If Casing is cemented, show amounts & types used NONE

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NONE

Depths & thickness of water zones with description of water when possible:

Fresh, Clear, Salty, Sulphur, Etc. NONE

Depths gas encountered: NONE

Type & amount of coke breeze used: 99.9% CARBON, CARBO 60 = 1233#

Depths anodes placed: 5 250 T0295

Depths vent pipes placed: 0' TO 300'

Vent pipe perforations: 240' TO 300'

Remarks: _____

RECEIVED

FEB 04 1991

OIL CON. DIV
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.

If Federal or Indian, add Lease Number.

WELL TYPE GROUNDBED DATA

DATA SHEET NO.

COMPANY Ladd Petroleum

JOB No. 13123 DATE: 1-5-88

WELL, KROFF AIF

PIPELINE:

LOCATION: SEC. 13 TWP. 27N RGE. 10W CO. SAN JUAN STATE N. Mex

ELEV. _____ FT: ROTARY 300' FT: CABLE TOOL 0 FT: CASING 0

GROUND BED: DEPTH 300' FT. DIA. 6 1/4 IN. GAB 1233 LBS. ANODES 5 LINDA String

DEPTH, FT.	DRILLER'S LOG	EXPLORING ANODE TO STRUCTURE			NO COKE	WITH COKE	DEPTH TOP OF ANODES		
		E	I	R			NO.	FT.	
00	Sand		0.4						
5			0.6						
10			0.6						
15			0.7						
20			0.9						
25			0.2						
30			0.1						
35			0.1						
40			0.3						
45			0.2						
50			0.3						
55			0.4						
60			0.3						
65			0.3						
70			0.7						
75			0.9						
80			0.8						
85			1.1						
90		Sand & Shale	1.3						
95			1.1						
200	1.2								
5	0.6								
10	0.5								
15	0.3								
20	0.3								
25	0.4								
30	1.0								
35	1.4								
40	1.0								
45	0.9								
50	0.7						250		
55	0.6						↑ Sand ↓		
60	1.1								
65	1.7								
70	1.5				5.7	14.2			
75	1.4								
80	1.5								
85	1.5								
90	1.6								
95	1.4								
200	1.2						295		

GROUNDSED RESISTANCE: (1) VOLTS 12.60 - AMPS 1.2 - 0.88 OHMS

(2) **VIBROGROUND** **CHAS**