

30-045-28395

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 copies to OCD Aztec Office)

Operator Bonnerille Fuels Corp. Location: Unit _____ Sec. 14 Twp 22 Rng 11

Name of Well/Wells or Pipeline Serviced Fullerton Fed. #14-32

Elevation _____ Completion Date 5-17-91 Total Depth 300' Land Type* F

Casing, Sizes, Types & Depths NA-None

If Casing is cemented, show amounts & types used NA-None

If Cement or Bentonite Plugs have been placed, show depths & amounts used
NA-None

RECEIVED
JUN 7 1991

OIL CON. DIV.

DIST. 0

Depths & thickness of water zones with description of water when possible:

Fresh, Clear, Salty, Sulphur, Etc. First & only clear water
streak at 140' Deep

Depths gas encountered: NA-None

Type & amount of coke breeze used: Loresco SW 99.9% Carbon = 1,100 LBS.

Depths anodes placed: 235', 245', 255', 265', 275' + 285' Deep.

Depths vent pipes placed: 0 to 300' Deep

Vent pipe perforations: Laser Cut Slots From 160' to 300' Deep.

Remarks: Solid 1" dia. PVC vent pipe from 0' to 160' Deep

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

WELL TYPE GROUND BED DATA

DATA SHEET NO. One(1)

COMPANY BONNEVILLE FUELS CORP. JOB NO. 751-00118 DATE: 5-17-91
 WELL: AFULLERTON FED #74-32 PIPELINE: _____
 LOCATION: SEC. 14 TWP. 27 RGE. 11 CO. SAN JUAN STATE NM
 ELEV. _____ FT: ROTARY 300' FT: CABLE TOOL -0- FT: CASING -0- FT.
 GROUND BED: DEPTH 300' FT. DIA. 6" IN. GAS 1,100 LBS. ANODES LIP A STRING

DEPTH. FT.	DRILLER'S LOG	EXPLORING ANODE TO STRUCTURE			NO COKE	WITH COKE	ANODE NO.	DEPTH. TOP OF ANODES
		E	I	R				
	FIRST WATER 140'							
150	0-10 SAND		5.0					
155	10-25 SHALE		4.8					
160	25-60 SAND		4.6					
165	60-140 SANDY SHALE		4.2					
170	140-190 SAND		4.3					
175	190-300 SANDY SHALE		4.1					
180			4.4					
185			4.5					
190			4.1					
195			4.3					
200			3.9					
205			4.1					
210			3.5					
215			4.1					
220			3.8					
225			4.4					
230			4.1					
235			4.2					235
240			4.0					
245			4.7					245
250			4.4					
255			4.8					255
260			4.5			5.4	23.4	265
265			5.2					
270			4.9					
275			5.4					275
280			4.8					
285			5.4					285
290			4.9					
295			5.3					
300			5.3					

RECEIVED

JUN 7 1991

OIL CON. DIV
DIST. 3GROUND BED RESISTANCE: (1) VOLTS 12.35 - AMPS 23.4 - 5.3 OHMS(2) VIBROGROUND 53 OHMS

GENERAL CATHODIC PROTECTION SERVICES CO.

A LUKEV'S COMPANY