DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS NORTHWESTERN NEW MEXICO

(Submit 3 Copies to OCD Aztec Office)

Operator: <u>BLACKWOOD & NICHOLS CO.</u> Location: Unit <u>N</u> , Sec. <u>36</u> , Twp <u>31N</u> , Rng <u>6W</u> .
Name of Well/Wells or Pipeline Serviced NEBU 481
Elevation 6400'± Completion Date 6-14-93 Total Depth 270' Land Type* Surface: S Mineral: E-505-6
Casing, Sizes, Types & Depths 8-5/8" SCH 40 P.V.C 100', 7 7/8 'Ο Ρε Α Ησις.
If Casing is cemented, show amounts & types used 20 sks Portland Zia I-II
If Cement or Bentonite Plugs have been placed, show depths & amounts usedN/A
Depths & thickness of water zones with description of water when possible:
Fresh, Clear, Salty, Sulphur, Etc. N/A
Depths gas encountered: N/A OILCON: DIV.
Type & amount of coke breeze used: Asbury Flo-Coke
Depths anodes placed: 255' to 150' - 10 anodes
Depths vent pipes placed: Bottom to 4' above ground level
Vent pipe perforations: 270' to 130'
Remarks: Damp spot at 160'
If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.
*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee. If Federal or Indian, add Lease Number.

Title: Operations Engineer Date: 8/11/93

BLACKWOOD & NICHOLS CATHODIC GROUND BED DRILLERS REPORT

P# <u>SN-25</u> WELL# <u>NEB,U, #48</u> /				-N- s 36 T 31 R6	
DEPTH	STRATA	NOTES	DEPTH	STRATA	NOTES
5-100	Casing				
	Sundstane	·			
10-125	Black Shal				
25-145	Grey Sang	Istone (Danga 148')			
45-185	lites de	V.			
185-205	brig Sang	Stone (Damy 199)			
-05-28	brey Sha				
80-285	breg Sand	tone			
			,		
	· · · · · · · · · · · · · · · · · · ·				
	Marian				
	200				

INSPECTOR May D. M. Fach of