

30-045-28424

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 copies to OCD Aztec Office)

Operator Bonnerville Fuels Corp. Location: Unit Sec. 11 Twp 22 Rng 11

Name of Well/Wells or Pipeline Serviced Fullerton Fed. #11-41

Elevation Completion Date 5-16-91 Total Depth 300' Land Type* F

Casing, Sizes, Types & Depths NA-None

If Casing is cemented, show amounts & types used NA-None

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NA-None

Depths & thickness of water zones with description of water when possible:

Fresh, Clear, Salty, Sulphur, Etc. First & only (Clear) Water

Streak at 120 Foot Depth

Depths gas encountered: NA-None

Type & amount of coke breeze used: CARBON-99.9% Carbon-1200 LBS.

Depths anodes placed: 230', 240', 250', 260', 270' & 280' Deep

Depths vent pipes placed: 0 to 300' Deep

Vent pipe perforations: Laser Cut Slots From 140' to 300' Deep

Remarks: Solid 1" dia. pipe from 0' to 140' Deep

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

WELL TYPE GROUNDED DATA

DATA SHEET NO. One(1)

COMPANY BONNEVILLE FUELS CORP. JOB No. 751-00118 DATE: 5-16-91
 WELL: FULLERTON FGD #11-41 PIPELINE: _____
 LOCATION: SEC 11 TWP. 27 RGE. 11 CO. SAN JUAN STATE NM
 ELEV. _____ FT: ROTARY 300' FT: CABLE TOOL -0' FT: CASING -0' FT.
 GROUNDED: DEPTH 300' FT. DIA. 6" IN. GAS 1200 LBS. ANODES LIDA STRING

DEPTH, FT.	DRILLER'S LOG	EXPLORING ANODE TO STRUCTURE			NO COKE	WITH COKE	ANODE NO.	DEPTH, TOP OF ANODES
		E	I	R				
	FIRST WATER 120'							
150	0-60' SAND		4.2					
155	60-110 SHALE		4.4					
160	110-140 SANDY SHALE		4.2					
165	140-200 SHALE - SOME SAND		4.6					
170	200-300 SANDY SHALE		4.5					
175			3.9					
180			4.5					
185			4.5					
190			4.6					
195			4.3					
200			4.4					
205			4.1					
210			4.1					
215			4.0					
220			4.1					
225			4.1					
230			4.2					230
235			4.3					
240			4.1					240
245			4.2					
250			4.4					250
255			4.5					
260			4.6		4.6	13.9		260
265			4.1					
270			4.2					270
275			4.4					
280			4.4					280
285			4.0					
290			3.9					
295			3.9					
300			3.1					

RECEIVED

JUN 7 1991

OIL CON. DIV.
DIST. 3

ANODES

GROUNDED RESISTANCE: (1) VOLTS 12.5 - AMPS 13.9 - 90 OHMS(2) VIBROGROUND 90 OHMS

GENERAL CATHODIC PROTECTION SERVICES CO.

A LUKENS COMPANY