If Federal or Indian, add Lease Number.

Signed by:

プローロステラウ #477/ 30-0 DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELL NORTHWESTERN NEW MEXICO

(Submit 3 Copies to OCD Aztec Office)

Operator: BLACKWOOD & NICHOLS CO. Location: Unit H, Sec. 29, Twp 30N, Rng 7W. Name of Well/Wells or Pipeline Serviced NEBU 477, 6 Elevation 6340' Completion Date 7-12-93 Total Depth 392' Land Type* Surface: F Mineral: SF-079060 Casing, Sizes, Types & Depths 8-5/8" SCH 40 P.V.C. - 100', 7 7/8" OPEN HOLE. If Casing is cemented, show amounts & types used 20 sks Portland Zia I-II If Cement or Bentonite Plugs have been placed, show depths & amounts used N/A Depths & thickness of water zones with description of water when possible: Fresh, Clear, Salty, Sulphur, Etc. Not enough for sample, moisture at 140' Depths gas encountered: N/A Type & amount of coke breeze used: Asbury Recarburized - 112 sx Depths anodes placed: 138' to 355' Depths vent pipes placed: 395' to 4' above ground level Vent pipe perforations: 95' to 395' Groundbed located 140' N 50° E of NEBU 477 If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included. *Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.

Title: Operations Engineer Date: 3/11/93

13

CP#55/8 WELL#NEB 6-29

s 29 T30 1/ R7/

P# <u>05/8</u>	2 × 1 1 × 1 1 × 1				
DEPTH	STRATA	NOTES	DEPTH	STRATA	NOTES
<i>S'</i>					
10:	/\				
20'	11			· · · · · · · · · · · · · · · · · · ·	
	7				
30'	4				
40'	113				
	7				
50'	8				
	9				
60'	V				•
<u> </u>	4				
701	~ ~	·	1		
	3				
80'	9				
901					
100'	<u> </u>				
	(
	.,				

DRILLER gono murling

INSPECTOR Jul Matysek

CP#55-18 WELL# NEBIL #477+#6

s 29 T 30 RO

C1 π					
DEPTH	STRATA	NOTES	DEPTH	STRATA	NOTES
0-100	Lasta a	/		<u> </u>	
100-135	Greg Said	for. (Damp 140)	,		
135-145					
145-160	brug San	Istone			
160-178	- Grey Shap	(e,,			
175-28	5 Grig San	Iston.			
285-290	breg Shal	<u> </u>			
2 90 - 33%	- brig Sang	Istone			
335-35		V-e, ,			
350-410	Grey San.	stone			
		·			
		Í			
		/			
		,			
		,			

DRILLER The

INSPECTOR

). Cran