SW-23

#415 30-039 - 24320 DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS NORTHWESTERN NEW MEXICO

(Submit 3 Copies to OCD Aztec Office)

Operator: BLACKWOOD & NICHOLS CO. Location: Unit <u>G</u> , Sec. <u>2</u> , Twp <u>30N</u> , Rng <u>7W</u> .
Name of Well/Wells or Pipeline Serviced NEBU 415, 14
Elevation 6320' Completion Date 6-16-93 Total Depth 375' Land Type* Surface: S Mineral: E-289-3
Casing, Sizes, Types & Depths 8-5/8" SCH 40 P.V.C 100' 7 7/8" OPEN HOLE.
If Casing is cemented, show amounts & types used 20 sks Portland Zia I-II - 90#
If Cement or Bentonite Plugs have been placed, show depths & amounts usedN/A
Depths & thickness of water zones with description of water when possible:
Fresh, Clear, Salty, Sulphur, Etc. Fresh, not enough for water sample. Aug 2 6 1993
Depths gas encountered: N/A OIL CON. The Contract of the Contr
Type & amount of coke breeze used: Asbury Recarburized, 5,300#
Depths anodes placed: 355' to 145' - 15 anodes
Depths vent pipes placed: 375' to 3' above ground level
Vent pipe perforations: 375' to 115'
Remarks: Drilling water from Frances Canyon.
If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.
*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee. If Federal or Indian, add Lease Number.

Title: Operations Engineer Date: 8/u/93

BLACKWOOD & NICHOLS CATHODIC GROUND BED DRILLERS REPORT

P#SN-23 WELL# N.E.B.U. # 415, #14

G S 2 T 30 R7

P# <u>=</u>	WELL# / / / LES			O	S
DEPTH	STRATA	NOTES	DEPTH	STRATA	NOTES
5-100	Casing				
100-145	Sanston	(Days (0 145)			
145-180	Sandston. Dluck Shale	1 6 75			
180-220	bry Sant	stone (H20@ 190)			
120-239	bry Sant	, ,			
235-270	Greg Sant	tone			
-70-32	o brey Sha	le,			
120-33	5 brey San	Istone			
335-30	o been She	10,,			
360 - 380	Grey Sa	rdston a			
			·		
		·		<u> </u>	*

RILLER Th

INSPECTOR May D. M. Facland