

625
30-039-24926 E 2247W
DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Location: Unit K Sec. 24 Twp 30 Rng 6

Name of Well/Wells or Pipeline Serviced J.J. 30-6 # 489

Elevation 6550 Completion Date 8-16-91 Total Depth 360 Land Type F

Casing Strings, Sizes, Types & Depths 100' ish 40 8" PVC

If Casing Strings are cemented, show amounts & types used

20 sacks Cement

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NO

Depths & thickness of water zones with description of water: Fresh, Clear, Salty, Sulphur, Etc. 150' fresh

RECEIVED
FEB 24 1992
OIL CON. DIV.
DIST. 3

Depths gas encountered: NO

Ground bed depth with type & amount of coke breeze used: 360' Ashbury 49 sacks

Depths anodes placed: 340' 330' 320' 310' 300' 290' 280' 270' 260' 235' 225' 215'

Depths vent pipes placed: 360'

Vent pipe perforations: 1' apart, perforated bottom 260'

Remarks: _____

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

PDS#		P/L NAME(s), NUMBER(s)										
2247-w		S.T. 30-6 #489										
WO #	TOTAL	VOLTS	AMPS	- OHMS	DATE	NAME						
L706		9.72	18.4	.53	8-16-91	L.S.E						
REMARKS (notes for construction log)												
Water was at 150'. Perforated bottom 260' of Vent pipe. Hole bridged off at 160'. Cleaned hole out with water + air pressure.												
DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	FULLY COKE'D
100			295	3.7		490			685			
105			300	3.4	(5)	495			690			
110			305	3.5		500			695			
115			310	3.5	(4)	505			700			
120			315	3.2		510						
125			320	3.1	(3)	515						
130			325	3.2		520			1	340	3.4	5.1
135			330	3.3	(2)	525			2	330	3.3	5.3
140			335	3.2		530			3	320	3.5	5.2
145			340	3.3	(1)	535			4	310	3.5	5.2
150	2.6	(13)	345	2.5		540			5	300	3.6	5.1
155	2.4		350	2.1		545			6	290	3.7	4.4
160	2.5		355	2.0		550			7	280	2.8	4.1
165	2.9		360	TD		555			8	270	2.6	4.4
170	3.2		365			560			9	260	2.6	3.8
175	3.7		370			565			10	235	2.9	3.6
180	4.1		375			570			11	225	2.9	3.7
185	4.1		380			575			12	215	3.2	4.1
190	3.7		385			580			13	150	2.5	4.4
195	3.8		390			585			14			
200	4.0		395			590			15			
205	2.7		400			595			16			
210	3.1		405			600			17			
215	3.3	(12)	410			605			18			
220	3.0		415			610			19			
225	2.8	(11)	420			615			20			
230	2.8		425			620			21			
235	2.5	(10)	430			625			22			
240	2.4		435			630			23			
245	1.8		440			635			24			
250	1.7		445			640			25			
255	2.5		450			645			26			
260	2.7	(9)	455			650			27			
265	2.7		460			655			28			
270	2.7	(8)	465			660			29			
275	2.8		470			665			30			
280	2.8	(7)	475			670						
285	3.2		480			675						
290	3.1	(6)	485			680						

DISTRIBUTION - original - permanent CPB FILE

copy - Division Corrosion Supervisor

copy - Region Corrosion Specialist