

32- 30-045-28257

22- 30-045-30898

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

(Submit 3 copies to OCD Aztec Office)

Operator Bonneville Fuels Corp. Location: Unit Sec. 22 Twp 27 Rng 11

Name of Well/Wells and Pipeline Serviced Scott "E" Fed. #22-32 + #22-22

Elevation ? Completion Date 5-14-91 Total Depth 300' Land Type* F

Casing, Sizes, Types & Depths PVC Casing 8" I.D., 8 5/8" O.D.,
Schedule 40, B.E. to 25' Deep.

If Casing is cemented, show amounts & types used NA-None

RECEIVED
JUN 7 1991

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NA-None

OIL CON. DIV

Depths & thickness of water zones with description of water Dist. 3 possible:

Fresh, Clear, Salty, Sulphur, Etc. First + only Water (Clear) Streak
at 95 Foot Depth.

Depths gas encountered: NA-None

Type & amount of coke breeze used: CARBO 40, 99.9% Carbon, 1,500 LBS,

Depths anodes placed: 200', 210', 220', 230', 240' and 250' Deep.

Depths vent pipes placed: 0' to 300' Deep.

Vent pipe perforations: Laser Cut Slots from 100' to 300' Deep.

Remarks: Solid 1" diameter PVC (vent) pipe from 0' to 100'
Deep.

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

WELL TYPE GROUNDBED DATA

DATA SHEET NO. One(1)

COMPANY BONNEVILLE FUELS CORP JOB No. 751-00118 DATE: 5-14-91
 WELL: SCOTT "E" FED. #22-32 PIPELINE: _____
 LOCATION: SEC. 22 TWP. 27 RGE. 11 CO. SAN JUAN STATE NM
 ELEV. _____ FT: ROTARY ✓ FT: CABLE TOOL — FT: CASING 25' FT.
 GROUNDBED: DEPTH 300 FT. DIA. 6" IN. GAS CARBON LBS. ANODES ANODE STRING

DEPTH. FT.	DRILLER'S LOG	EXPLORING ANODE TO STRUCTURE			NO COKE	WITH COKE	ANODE NO.	DEPTH. TOP OF ANODES
		E	I	R				
150	FIRST WATER 95'							
155	SANDY SHALE		4.1					
160			4.4					
165	SHALE		4.7					
170			4.8					
175			4.9					
180			5.3					
185			4.9					
190			5.0					
195			4.5					
200			4.6					200
205			4.5					
210			4.3					
215			4.0					
220			3.8					
225			3.8					
230			3.5					
235			3.7					
240	SANDY SHALE		3.5					
245			4.0					
250			3.9					250
255			4.3					
260			4.1					
265	SHALE		4.4					
270			3.9					
275			4.4					
280	SAND		4.2					
285			4.2					
290			4.1					
295			3.8					
300	T-D. 300'							

RECEIVED
 JUN 7 1991
 OIL CON. DIV.,
 DIST. 3

GROUNDBED RESISTANCE: (1) VOLTS 12.43 - AMPS 16.28 - OHMS 0.76(2) VIBROGROUND 76 OHMS

GENERAL CATHODIC PROTECTION SERVICES CO.

A LUKENS COMPANY