

698

30-045-27768

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

2340W

Operator Meridian Oil Location: Unit H Sec. 8 Twp 30 Rng 10Name of Well/Wells or Pipeline Serviced Kelly BTRElevation 6328 Completion Date 12-8-91 Total Depth 462 Land Type FCasing Strings, Sizes, Types & Depths 8" PVC surface casingIf Casing Strings are cemented, show amounts & types used yes, with 23Bags of neat cement

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NADepths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. 80' freshDepths gas encountered: NAGround bed depth with type & amount of coke breeze used: 462'2500 lbs Hsberg 4518 fls coke 800 lbs loose type. S.Depths anodes placed: 445, 436, 427, 418, 409, 400, 391, 275, 225, 215, 205, 195Depths vent pipes placed: 462'Vent pipe perforations: Bottom 350'

Remarks: _____

RECEIVED

FEB 24 1992

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.

If Federal or Indian, add Lease Number.

2340W

CPS GROUND BED CONSTRUCTION WORKSHEET

2340W

CPS#	P/L NAME(s), NUMBER(s)					
2238W	Kelly BIR					
WD #	TOTAL	VOLTS	AMPS	- OHMS	DATE	NAME
K333		11.80	28.8	.409	12-8-91	KD, MW

REMARKS (notes for construction log)
 Set 80' casing, 23 # of Bags of cement, Hit water at 80', caught water so
 perforated Bottom 250', 8 coresco, 130 asbury

DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE
	ANODE	#		ANODE	#		ANODE	#		ANODE	#
100	1.8		295	.7		490			685		
105	1.7		300	.7		495			690		
110	1.3		305	.7		500			695		
115	.9		310	.6		505			700		
120	.5		315	.5		510			ANODE	DEPTH	NO
125	.6		320	.6		515			*		COKE
130	.6		325	.7		520			1	445	2.3
135	.8		330	.5		525			2	436	2.4
140	1.0		335	.5		530			3	427	2.2
145	1.3		340	.7		535			4	418	2.2
150	1.7		345	.7		540			5	409	2.1
155	1.5		350	.7		545			6	400	1.8
160	1.4		355	1.0		550			7	391	1.5
165	1.1		360	.8		555			8	275	1.3
170	.8		365	.6		560			9	225	1.3
175	1.0		370	.6		565			10	215	1.2
180	1.3		375	.6		570			11	205	1.2
185	1.3		380	.6		575			12	195	1.4
190	1.5		385	.4		580			13		
195	1.4	12	390	1.3		585			14		
200	1.4	9	395	1.7		590			15		
205	1.3	11	400	1.7		595			16		
210	1.2	10	405	1.9		600			17		
215	1.2		410	2.0		605			18		
220	1.2		415	2.2		610			19		
225	1.3	9	420	2.2		615			20		
230	1.2	*	425	2.2		620			21		
235	.9		430	2.2		625			22		
240	.4		435	2.3		630			23		
245	.4		440	2.3		635			24		
250	.5		445	2.2	1	640			25		
255	.7		450	2.4		645			26		
260	.6		455	2.8		650			27		
265	.8		460	457 TO		655			28		
270	1.3		465	462 TO		660			29		
275	1.3	8	470			665			30		
280	1.0		475			670					
285	.7		480			675					
290	.7		485			680					

DISTRIBUTION -- original -- permanent CPS FILE
 copy -- Division Correction Supervisor
 copy -- Region Correction Specialist