

645

30-045-27866

E

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

2269

Operator Meridian Oil Location: Unit 6 Sec. 24 Twp 28 Rng 10Name of Well/Wells or Pipeline Serviced 1st CLADAHAN #551Elevation 5875 Completion Date 12-5-91 Total Depth 395' Land Type FCasing Strings, Sizes, Types & Depths 8" PVC SURFACE CASING
9.5" DEEPIf Casing Strings are cemented, show amounts & types used Yes, with
22 BAGS NEAT CEMENTIf Cement or Bentonite Plugs have been placed, show depths & amounts used
NODepths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. FRESH 130'Depths gas encountered: NOGround bed depth with type & amount of coke breeze used: 395' with
5400 lbs of LORESCO Type 50Depths anodes placed: 375, 360, 350, 340, 330, 320, 310, 285, 275, 265, 255, 2Depths vent pipes placed: 395'Vent pipe perforations: bottom 270

Remarks: _____

RECEIVED

FEB 24 1992

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

CPS# 2269.~	P/L NAME(s), NUMBER(s) M ² CLANAHAN #551					
WO # R444	TOTAL	VOLTS 11.82	AMPS 29.1	- OHMS 406	DATE 12.5.91	NAME mru
REMARKS (notes for construction log)						
95 CASING 22 SACKS CEMENT						
G24-28-10 WATER AT 130' Drilled 400', LOGGED 395						
Perforated bottom 270'						
54 BAGS LORESCO						

DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	
	ANODE	#		ANODE	#		ANODE	#		ANODE	#	
100			295	1.0		490			685			
105			300	1.1		495			690			
110			305	2.5		500			695			
115			310	3.1-		505			700			
120			315	3.4		510			ANODE	DEPTH	NO	FUL
125	1.4		320	3.3-		515			*		COKE	COI
130	1.6		325	3.4		520			1	375	2.6	5
135	1.6		330	3.5-		525			2	360	3.0	6.
140	1.6		335	3.7		530			3	350	3.5	7
145	2.0		340	3.6-		535			4	340	3.6	7.
150	2.0		345	3.9		540			5	330	3.5	7.
155	2.0		350	3.5-		545			6	320	3.4	7.
160	2.2		355	3.4		550			7	310	3.1	6.
165	2.2		360	2.8-		555			8	285	4.0	8.
170	2.2		365	2.2		560			9	275	4.0	8.
175	2.6		370	2.5		565			10	265	3.5	7.
180	2.1		375	2.6		570			11	255	3.7	7.
185	1.9		380	1.8		575			12	245	3.4	7.
190	1.8		385	2.0		580			13			
195	1.6		390	1.7		585			14			
200	1.5		395		395	590			15			
205	1.0		400			595			16			
210	1.1		405			600			17			
215	1.5		410			605			18			
220	2.0		415			610			19			
225	1.4		420			615			20			
230	1.2		425			620			21			
235	2.4		430			625			22			
240	2.9		435			630			23			
245	3.4-		440			635			24			
250	3.5		445			640			25			
255	3.8-		450			645			26			
260	3.8		455			650			27			
265	3.5-		460			655			28			
270	3.9		465			660			29			
275	4.0-		470			665			30			
280	3.9		475			670						
285	3.9-		480			675						
290	1.0		485			680						

DISTRIBUTION - original - permanent CPS FILE
 copy - Division Corrosion Supervisor
 copy - Region Corrosion Specialist