162 - 30 - 039 - 82372 243 - 30 - 039 - 24495 126 - 30 - 039 - 06856

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 copies to OCD Aztec Office)

Operator Union Oil Company of California Location: Unit Sec. 27 Twp27N Rng6W
Name of Well/Wells or Pipeline Serviced Rincon #162 PC Rincon #126 DK
Rincon #243 FC
Elevation 6583' Completion Date 11/6/89 Total Depth 300! Land Type* F
Casing, Sizes, Types & Depths None
m reriwe m
If Casing is cemented, show amounts & types used None WAIL & 1990.
If Cement or Bentonite Plugs have been placed, show depths & Offic Outs used  None
Depths & thickness of water zones with description of water when possible:
Fresh, Clear, Salty, Sulphur, Etc. 120' SEE ATTACHED SHEET
Depths gas encountered: NA
Type & amount of coke breeze used: Carbo 60 3000 lbs
Depths anodes placed: 205' to 260'
Depths vent pipes placed: 260'
Vent pipe perforations: 205'
Remarks: El Paso Natural Gas Co. was the operator at the time this ground bed was installed.
Third ground bed installed at this location.
If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.
*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.  If Federal or Indian, add Lease Number.

## Cathodic Protection Services Company P. O. Box 388 Farmington, New Mexico 87499 1608 Schofield Lane Farmington, New Mexico 87401 (505) 325-1946

February 2, 1990

FEB 5 1990
UNOCAL, BLOOMFIELD

Unocal Corporation 3300 N. Butler, Suite 201 Farmington, NM 87401

Attention: Mr. Steve Gregory

Subject: Major Water Zones in Cathodic Protection Deep-Well Groundbeds

Dear Mr. Gregory:

Per your recent request for information concerning the cathodic protection deep-well groundbeds for your well casings in the San Juan Basin area, we are pleased to submit the following information.

Township & Range	Depths Ranging From Shallowest to Deepest	Average Depth	Average Thickness of Water Zone			
T-25N - R-10W	110' - 140'	122.5'	20'			
T-25N - R-11W	60' - 140'	93.31	45'			
T-26N - R-7W	80' - 150'	112.5'	30 <b>'</b>			
T-27N - R-7W	80' - 200'	123.3'	22.5'			
T-27N - R-6W	80' - 200'	131.1'	30'			

This data reflects information supplied by the drilling logs acquired at the time the wells were drilled. The depths shown are based on the type of sand which was being extruded from the drilled hole and the dampness of the sand.

The thickness of the water zones are determined by the change in the strata which was being drilled.

It has been a pleasure providing this information to your company. If you have any further questions or desire additional information, please do not hesitate to contact us.

Sincerely,

Cathodic Protection Services Company

John Kerr, Corrosion Technician

cc: Mike Tabet



"是一个一个一个

	, )	75/						
OMPAI	NY Unocah	<u> </u>	JOB	No. C	20027 c	DATE: .	//- 4	<u> </u>
/ELL: _	RINCON # 243	PIPE	LINE:		4			
00 1 71	RINCON # 243  ON: SEC 27 TWF. 27 POR. 6		210	1	7 (5×7		1127	'ex
LEV	FT: ROTARY 300 PT:	CABLE	TCOL .		PT	: CAS	ING	<u> </u>
ROUN	DBED: ORPTH 300 PT. OU. 6 N.	. GAB _	3000	L#3.	ANCDES	_2_	DA S	>TRIWC
			ORING A				ANODE	<del>.                                      </del>
DEPTH,	DRILLER'S LCG				COKE	1	1	DEPTH,
FT.	CHILLER'S CCG		1 1	<u> 7</u>	i	I	] 100.	ANODES
<u>'</u>	FREST WATER 120'		<del>                                     </del>	<del></del>		<del></del>	1	<del></del>
<del></del>	PRIST WATER 120'	<u> </u>	<del> </del>	<del> </del>	<del></del>	<del></del>	<u> </u>	<del>-</del>
		1	1			1		1
200		1	15.2					1
5		1	150	i		1	1	1
10		Ī	1 4.9		1	1	1	1
5	Top of LIDA Andors		15.2		15.5	6.0	1	1215
20			15.3	<u> </u>		<u> </u>	1	!c
		<u> </u>	1 4.9	!			!	!
30	****		4.0		1 450	<u> </u>	TRINI	<del></del>
5			4.1	-			!	<del> </del>
40			13.9	<del>                                     </del>		-		<del> </del>
			3.6	<del>                                     </del>		<del></del>	<del>-                                    </del>	+==
50.			4.0	<u> </u>		<del></del>	-!	250
5			4.0	<del> </del>	<del></del> -			<del></del>
60			3.6	<del>                                     </del>		<del></del>	<del></del>	<del></del>
70		-	2.4		<del>-i</del>	<del>-i</del>		
<u>- 70</u>		<del></del>	1 2.3		<del></del>	-		
90	•		1 2.0		<del>- i</del>	<del>-  </del>	<del>-i</del>	<del>-i</del>
5	-		1.9		<del>- i</del>	<del>-i</del>	1	i
90		1	1 1. 9	Ī	1	1	1	i
5			11.6		ı		<u> </u>	
300	T.D. 300		<u> </u>	<u> </u>		1	<u> </u>	
			_	<u> </u>		<u> </u>	_!	
				<del></del>			_{	
		_	_	<del></del>				
<b></b>				<del></del> -				
	V.P 260	<del></del>		<del></del>		<del>-                                    </del>	<del></del>	<del></del>
<del> </del>	11.89, 205	- <del> </del>		<del>                                     </del>	<del>i</del>	- <del> </del>	i	<del>-i</del>
	(c)	<u> </u>	<del>-                                    </del>	1	1,:	1	<u> </u>	<u> </u>
	No. 14 AMERICA		i					1
				_!				
	32.00			<u> </u>			_!	<u> </u>
				<del></del>		<del></del>	_	<u> </u>
				1			_	<u> </u>
						<del> </del> -		<del>- </del>
		_		<del></del>				
<del> </del>		_						
<b> </b>							<u> </u>	

GROUNDEED RESISTANCE. (1) VOLTS 11.8 - AMPS 6.0 - 1.96 OHMS

(2) VIBROGROUND \_\_\_\_\_ OHME

GENERAL CATHODIC PROTECTION SERVICES CO.

