

716

30-039-24427 E

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

9010 W

Operator Murphy Oil Location: Unit N Sec. 14 Twp 31 Rng 6Name of Well/Wells or Pipeline Served Pass # 314Elevation 6345 Completion Date 10-26-91 Total Depth 445 Land Type FCasing Strings, Sizes, Types & Depths 60' 40' 8" PVC

If Casing Strings are cemented, show amounts & types used

12 sacks Cement

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NO

Depths & thickness of water zones with description of water: Fresh, Clear,

Salty, Sulphur, Etc. Dry hole

RECEIVED

FEB 24 1992

Depths gas encountered: NO

OIL CON. DIV

DIST

Ground bed depth with type & amount of coke breeze used:

445' Ashury 76 sacksDepths anodes placed: 420' 410' 375' 365' 355' 345' 330' 320' 310' 300' 265' 25Depths vent pipes placed: 410'Vent pipe perforations: 1" apart Perforated bottom 280'Remarks: from 2nd anode.

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.

If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

CP# 4010	P/L NAME(s), NUMBER(s) L 214					
WO # 4442	TOTAL	VOLTS	AMPS	- OHMS	DATE	NAME
		12.45	19.8	.62	10-26-71	L.S.E.

REMARKS (notes for construction log)

7-10 Water table, Dry hole. Set 60' of 3" PVC casing Perforated bottom 250' from 2nd mode

DEPTH	LOG ANODE	ANODE *	DEPTH	LOG ANODE	ANODE *	DEPTH	LOG ANODE	ANODE *	DEPTH	LOG ANODE	ANODE *
100	3.2		295	2.3		490			685		
105	3.0		300	2.7	- 10	495			690		
110	2.6		305	2.6		500			695		
115	2.9		310	2.5	- 7	505			700		
120	3.0		315	2.2		510			ANODE	DEPTH	NO.
125	3.3		320	2.5	- 5	515			*		FULL
130	3.2		325	2.8		520					COKE
135	3.0		330	2.7	- 7	525			1	420	2.1
140	2.8		335	2.0		530			2	410	2.2
145	2.0		340	1.6		535			3	375	2.1
150	2.5		345	2.5	- 6	540			4	365	2.3
155	2.2		350	2.6		545			5	355	2.7
160	1.0		355	2.7	- 5	550			6	345	2.5
165	.8		360	2.7		555			7	330	2.7
170	.8		365	2.3	- 4	560			8	320	2.4
175	1.8		370	2.1		565			9	310	2.6
180	2.1		375	2.1	- 3	570			10	300	2.6
185	1.7		380	2.0		575			11	265	2.3
190	1.4		385	1.8		580			12	255	2.4
195	1.2		390	1.7		585			13		
200	1.1		395	1.6		590			14		
205	.8		400	1.6		595			15		
210	.7		405	2.0		600			16		
215	.8		410	2.2	- 2	605			17		
220	1.0		415	2.1		610			18		
225	.8		420	2.0	- 1	615			19		
230	.5		425	1.8		620			20		
235	1.1		430	2.0		625			21		
240	1.5		435	2.2		630			22		
245	2.2		440	2.0		635			23		
250	2.0		445		T.D.	640			24		
255	2.4	- 12	450			645			25		
260	2.3		455			650			26		
265	2.3	- 11	460			655			27		
270	1.6		465			660			28		
275	1.2		470			665			29		
280	1.4		475			670			30		
285	2.2		480			675					
290	2.3		485			680					

DISTRIBUTION: - original: - permanent: CPS FILE

copy - Division Correction Supervisor
copy - Region Correction Specialist