

717

30-039-24429

E

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

9014W

Operator Meridian Oil Location: Unit H Sec. 11 Twp 31 Rng 6

Name of Well/Wells or Pipeline Serviced Rosa # 217

Elevation 6425 Completion Date 10-15-91 Total Depth 461 Land Type F

Casing Strings, Sizes, Types & Depths 60' sch 40 8" PVC

If Casing Strings are cemented, show amounts & types used

12 sacks Cement

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NO

Depths & thickness of water zones with description of water: Fresh, Clear, Salty, Sulphur, Etc. Dry hole

RECEIVED
FEB 24 1992

Depths gas encountered: NO

Ground bed depth with type & amount of coke breeze used:

461 Ashbury 77 sacks

Depths anodes placed: 430, 420, 410, 400, 390, 380, 370, 345, 335, 320, 310, 300'

Depths vent pipes placed: 420'

Vent pipe perforations: 1" apart Separated bottom 310'

Remarks: from 2nd anode.

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

CPS# 9014	P/L NAME(S), NUMBER(S) Lara # 217					
WO # J616	TOTAL 12.45	VOLTS 16.6	AMPS 1.75	OHMS	DATE 10-15-91	NAME L.S.E.
REMARKS (notes for construction log)						

no water table, Dry hole. Set 60' of 8" PVC casing. Perforated bottom 310' from 2nd anode.

DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #
100	2.0		295	1.9		490			685					
105	1.8		300	2.1	-12	495			690					
110	1.7		305	2.2		500			695					
115	1.5		310	2.1	-11	505			700					
120	1.4		315	2.2		510			ANODE	DEPTH	NO.	FULL		
125	1.6		320	2.1	-10	515			"		COKE	COKE		
130	2.5		325	1.6		520			1	430	2.3	4.0		
135	2.3		330	1.7		525			2	420	2.5	4.3		
140	2.0		335	1.9	-9	530			3	410	2.3	4.0		
145	1.7		340	1.9		535			4	400	2.5	4.3		
150	.9		345	1.8	-8	540			5	390	2.2	4.2		
155	.7		350	1.7		545			6	380	2.6	4.4		
160	.8		355	1.6		550			7	370	2.4	4.1		
165	1.5		360	1.7		555			8	345	1.9	3.5		
170	1.0		365	2.2		560			9	335	1.9	3.5		
175	1.7		370	2.3	-7	565			10	320	2.1	3.9		
180	2.3		375	2.4		570			11	310	2.2	4.1		
185	1.6		380	2.3	-6	575			12	300	2.1	4.0		
190	1.4		385	2.1		580			13					
195	1.3		390	2.1	-5	585			14					
200	1.7		395	2.3		590			15					
205	2.0		400	2.1	-4	595			16					
210	1.9		405	1.9		600			17					
215	1.5		410	2.1	-3	605			18					
220	1.1		415	2.4		610			19					
225	1.1		420	2.5	-2	615			20					
230	1.0		425	2.4		620			21					
235	.9		430	2.3	-1	625			22					
240	.8		435	1.8		630			23					
245	.7		440	1.8		635			24					
250	.7		445	2.2		640			25					
255	.8		450	2.2		645			26					
260	.6		455	1.9		650			27					
265	.5		460	TD	461	655			28					
270	.5		465			660			29					
275	.5		470			665			30					
280	.5		475			670								
285	.7		480			675								
290	1.2		485			680								

DISTRIBUTION -- original -- permanent CPS FILE
 COPY -- Division Corrosion Supervisor
 COPY -- Region Corrosion Specialist