

30-039-24496

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Location: Unit L Sec. 29 Twp 31 Rng 5

Name of Well/Wells or Pipeline Serviced Rosa #229 23274

Elevation 6445 Completion Date 11-9-91 Total Depth 375 Land Type F

Casing Strings, Sizes, Types & Depths 60" sch 40 8" PVC

If Casing Strings are cemented, show amounts & types used

12 sacks Cement

If Cement or Bentonite Plugs have been placed, show depths & amounts used

68' to 38', 30' Cement plug

Depths & thickness of water zones with description of water: Fresh, Clear,

Salty, Sulphur, Etc. Dry hole

RECEIVED

FEB 24 1992

Depths gas encountered: 290'

OIL CON. DIV. I

Ground bed depth with type & amount of coke breeze used: DIST. 3

375' Tonasco 60 sacks

Depths anodes placed: 340, 330, 320, 310, 270, 255, 240, 225, 210, 195, 175, 155

Depths vent pipes placed: 330'

Vent pipe perforations: 1" apart Perforated bottom 240'

Remarks: from 2nd anode.

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

REMARKS (notes for construction log) Set 60' of 3" PVC casing, Perforate bottom 240' from 2" d Anode. NO water table, Dry hole. Encountered gas at 240', Placed 30' Cement Plug.

DISTRIBUTION - original - permanent CPS FILE
copy - Division Corrosion Supervisor
copy - Region Corrosion Specialist

copy - Division Corrosion Supervisor
copy - Region Corrosion Specialist