

619
30-039-24830

E
DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Location: Unit M Sec. 2 Twp 29 Rng 7

Name of Well/Wells or Pipeline Serviced SAN JUAN 29-7 #582

Elevation 6528 Completion Date 9-14-91 Total Depth 476 Land Type F

Casing Strings, Sizes, Types & Depths Yes "8" PVC SURFACE CASING
86' DEEP

If Casing Strings are cemented, show amounts & types used Yes 25

SACKS NEAT CEMENT

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NO

Depths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. DAMP 100 160, 310

Depths gas encountered: NO

Ground bed depth with type & amount of coke breeze used: 476' DEEP

with 72 (100lb) BAGS LORESCO Type SW

Depths anodes placed: 360 350 310 300 290 270 260 240 230 220 200 190

Depths vent pipes placed: 476'

Vent pipe perforations: bottom 360

Remarks: _____

RECEIVED

FEB 24 1992

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

JOB# 2241-w	P/L NAME (*), NUMBER (*) SAN JUAN 29-7 #582					
WO # L986	TOTAL	VOLTS	AMPS	- OHMS	DATE	NAME
		12.01	21.4	.56	4-14-91	MRW
REMARKS (notes for construction log)						
M2-29-7 SET 86' of 8" PVC surface CASING 25 SACKS CEMENT						
ELEV = 6528 Damp 100, 160, 310 NOT ENOUGH for sample						
perforated bottom 360'						
72 ADD LORESCO						

DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	
	ANODE	*		ANODE	*		ANODE	*		ANODE	*	
100			295	1.9		490			685			
105			300	1.9		495			690			
110			305	1.5		500			695			
115			310	1.4		505			700			
									ANODE	DEPTH	NO	FULLY
									*		COKE	COKE D
120			315	1.1		510			1	360	1.4	4.2
125			320	.9		515			2	350	1.9	4.5
130			325	.7		520			3	310	1.3	4.0
135			330	.6		525			4	300	1.8	4.8
140			335	.5		530			5	290	1.8	5.0
145			340	.9		535			6	270	2.0	5.5
150			345	1.4		540			7	260	2.5	6.1
55	1.9		350	1.8		545			8	240	2.6	6.7
160	2.6		355	1.6		550			9	230	2.8	7.0
165	2.2		360	1.4		555			10	220	2.5	6.3
170	1.9		365	.9		560			11	200	2.3	6.1
175	2.1		370	.5		565			12	190	2.0	5.7
180	1.8		375	.4		570			13			
185	1.8		380	.3		575			14			
190	2.0		385	.3		580			15			
195	2.1		390	.3		585			16			
200	2.3		395	.2		590			17			
205	2.1		400	.1		595			18			
210	2.0		405	.1		600			19			
215	2.1		410	.2		605			20			
220	2.5		415	.2		610			21			
225	2.2		420	.2		615			22			
230	2.8		425	.2		620			23			
235	2.6		430	.3		625			24			
240	2.6		435	.5		630			25			
245	2.1		440	1.0		635			26			
250	2.2		445	1.0		640			27			
255	2.2		450	1.0		645			28			
260	2.5		455	.9		650			29			
265	2.3		460	.5		655			30			
270	2.0		465	.5		660						
275	1.9		470	.5		665						
30	1.7		475	TD	476	670						
85	1.7		480			675						
290	1.8		485			680						

DISTRIBUTION - original - permanent CPS FILE
 copy - Division Corrosion Supervisor
 copy - Region Corrosion Specialist