

30-039-25013

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

229522

Operator MERIDIAN Oil Location: Unit A Sec. 34 Twp 31 Rng 5

Name of Well/Wells or Pipeline Serviced ROSA UNIT #269

Elevation 6743 Completion Date 9-30-91 Total Depth 405 Land Type SE 07877

Casing Strings, Sizes, Types & Depths 60' 8" PVC SURFACE CASING

If Casing Strings are cemented, show amounts & types used 12 SACKS

CLEAN CEMENT

If Cement or Bentonite Plugs have been placed, show depths & amounts used:

Depths & thickness of water zones with description of water: Fresh, Clear,

Salty, Sulphur, Etc. DRY

RECEIVED
FEB 24 1992

Depths gas encountered: OIL CON. DIV.

Ground bed depth with type & amount of coke breeze used: 405' 40 sacks

Louisa & 52 sacks Asbury 4518 Fls Coke

Depths anodes placed: 380, 370, 360, 350, 340, 330, 270, 260, 250, 240, 200, 170

Depths vent pipes placed: 370'

Vent pipe perforations: BOTTOM 230'

Remarks:

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

230
40 60 60
R2 2500

CPS# 2295	P/L NAME(s), NUMBER(s) ROSA UNIT # 269				
WO # L 488	TOTAL	VOLTS 11.4	AMPS 26.5	OHMS 43	DATE 9-30-91
NAME W.R. McGaha					

REMARKS (notes for construction log)

60' 8" PVC surface casing; 12 sacks;
No H₂O; Install 370' of 1" pvc and pipe & perf. bottom 230'. Depth 405', Log 400'.

* NOTE: Hole was not drilled 500' because of rig compressor problem.

DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE
ANODE	ANODE	#	ANODE	ANODE	#	ANODE	ANODE	#	ANODE	ANODE	#	ANODE	ANODE	#
100	3.9		295	2.0		490			685					
105	3.7		300	2.1		495			690					
110	3.7		305	1.9		500			695					
115	3.1		310	2.1		505			700					
120	2.7		315	2.8		510			ANODE	DEPTH				
125	3.1		320	2.6		515			*					
130	3.0		325	2.8		520			1	380	3.1	5.6		
135	3.5		330	3.4	6 ✓	525			2	370	3.3	6.1		
140	3.3		335	3.4	40 ✓	530			3	360	3.4	6.0		
145	3.2		340	3.4	5 ✓	535			4	350	3.6	6.1		
150	3.5		345	3.5	4 ✓	540			5	340	3.5	5.9		
155	4.0		350	3.4	44 ✓	545			6	330	3.4	5.7		
160	3.9		355	3.4		550			7	270	3.4	5.8		
165	3.8		360	3.4	3 ✓	555			8	260	3.7	6.2		
170	3.8	12 ✓	365	3.3	2 ✓	560			9	250	3.7	6.3		
175	3.6		370	3.2	2 ✓	565			10	240	3.5	6.2		
180	2.8		375	3.1		570			11	200	3.4	5.7		
185	1.7		380	3.1	1 ✓	575			12	170	4.0	6.8		
190	1.3		385	3.2		580			13					
195	3.1		390	3.4		585			14					
200	3.4	11 ✓	395	3.7		590			15					
205	3.3		400	3.5		595			16					
210	2.8		405		405	600			17					
215	2.6		410			605			18					
220	2.4		415			610			19					
225	2.8		420			615			20					
230	3.3		425			620			21					
235	3.4		430			625			22					
240	3.4	10 ✓	435			630			23					
245	3.6		440			635			24					
250	3.6	7 ✓	445			640			25					
255	3.6		450			645			26					
260	3.6	8 ✓	455			650			27					
265	3.5		460			655			28					
270	3.4	7 ✓	465			660			29					
275	3.1		470			665			30					
280	2.5		475			670								
285	2.1		480			675								
290	2.1		485			680								

DISTRIBUTION - original - permanent CPS FILE

70 3.0 85 1.2 copy - Division Corrosion Supervisor
 75 2.8 90 2.8 copy - Region Corrosion Specialist
 80 1.7 95 3.7