

694

30-039-25063

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICOOperator Meredian Oil Location: Unit M Sec. 7 Twp 31 Rng 5Name of Well/Wells or Pipeline Serviced Losa # 227Elevation 525 Completion Date 10-10-91 Total Depth 477 Land Type FCasing Strings, Sizes, Types & Depths 60" sch 40 8" PVC

If Casing Strings are cemented, show amounts & types used

12 sacks Cement

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NO

Depths & thickness of water zones with description of water: Fresh, Clear,

Salty, Sulphur, Etc. Dry hole

RECEIVED

FEB 24 1992

Depths gas encountered: NOOIL CON. DIV.
DIST. 2

Ground bed depth with type & amount of coke breeze used:

477' Ashbury, 85 sacksDepths anodes placed: 305' 295' 285' 275' 265' 255' 230' 220' 195' 185' 170' 155'Depths vent pipes placed: 295'Vent pipe perforations: 1" apart Perforated bottom 200'Remarks: from 2nd anode.

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

CPS# 2283w	P/L NAME (S), NUMBER (S) <i>Rosa #227</i>					
NO # K842	TOTAL	VOLTS 12.40	AMPS 23.0	OHMS .53	DATE	NAME L.S.E.

REMARKS (notes for construction log)

No water table, Dry hole. Set 60' of 8" PVC casing, Reseparated bottom 200' from 2nd anode.

DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	NO. COKE	FULLY COKE'D
100	3.0		295	3.0	-2	490			685							
105	3.2		300	2.8		495			690							
110	3.6		305	2.7	-1	500			695							
115	3.6		310	2.2		505			700							
120	4.0		315	2.0		510			ANODE	DEPTH	NO.					
125	3.5		320	2.0		515			"		COKE					
130	3.2		325	2.0		520			1	305	2.8	5.1				
135	3.7		330	2.0		525			2	295	3.1	6.2				
140	3.4		335	1.8		530			3	285	3.2	6.3				
145	3.6		340	1.7		535			4	275	3.1	5.7				
150	3.4		345	1.6		540			5	265	2.9	5.6				
155	2.6	-12	350	1.5		545			6	255	3.0	5.5				
160	2.3		355	1.4		550			7	230	2.9	6.1				
165	2.2		360	1.3		555			8	220	3.0	6.3				
170	2.8	-11	365	1.6		560			9	195	2.9	6.0				
175	2.7		370	1.9		565			10	185	3.1	6.4				
180	3.1		375	1.8		570			11	170	3.0	6.3				
185	3.1	-10	380	1.9		575			12	155	3.2	6.4				
190	2.7		385	2.3		580			13							
195	2.8	-9	390	1.8		585			14							
200	2.6		395	1.8		590			15							
205	2.4		400	2.1		595			16							
210	2.1		405	1.9		600			17							
215	2.8		410	1.6		605			18							
220	2.8	-8	415	1.6		610			19							
225	3.0		420	1.7		615			20							
230	2.9	-7	425	1.6		620			21							
235	2.5		430	1.6		625			22							
240	2.5		435	1.7		630			23							
245	2.6		440	2.2		635			24							
250	2.9		445	2.4		640			25							
255	2.9	-6	450	2.6		645			26							
260	2.9		455	2.3		650			27							
265	2.9	-5	460	2.1		655			28							
270	2.7		465	2.5		660			29							
275	2.9	-4	470	2.4		665			30							
280	3.0		475	TD	477	670										
285	3.0	-3	480			675										
290	3.0		485			680										

DISTRIBUTION - original - permanent CPS FILE

copy - Division Corrosion Supervisor

copy - Region Corrosion Specialist