

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 copies to OCD Aztec Office)

171M-30-039-25180

117 30-039-06976

Operator UNOCAL, Oil & Gas Division Location: Unit J Sec. 21 Twp 27N Rng 6W

Name of Well/Wells or Pipeline Serviced Rincon Unit #171M, Rincon Unit #117

Elevation 6528 GR Completion Date 11-16-92 Total Depth 300' Land Type* F

Casing, Sizes, Types & Depths N O N E

If Casing is cemented, show amounts & types used N O N E

If Cement or Bentonite Plugs have been placed, show depths & amounts used

750 lbs. Enviro plug coarse chips (0' - 50')

Depths & thickness of water zones with description of water when possible: Fresh, Clear,
Salty, Sulphur, Etc. 0' TO 80', 80' Thick (wet)

Depths gas encountered: N O N E

Type & amount of coke breeze used: 2500 lbs. SWB Petroleum Coke

Depths anodes placed: 209', 215', 221', 227', 233', 239', 245', 251', 257', 263'

Depths vent pipes placed: 0' to 300'

Vent pipe perforations: 1/8" diameter holes, 200' to 300'

Remarks: Lease #SF079366

First Ground bed installed at this location

If any of the above data is unavailable, please indicate so. Copies of all logs, including
Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available.
Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

RECEIVED
JAN 25 1993
OIL CON. DIV
DIST. 3

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)

Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER		5. LEASE DESIGNATION AND SERIAL NO SF - 079366
2. NAME OF OPERATOR Union Oil Company of California dba UNOCAL		6. IF INDIAN, ALLOTTEE OR TRIBE NAME N/A
3. ADDRESS OF OPERATOR P.O. Box 850, Bloomfield, New Mexico 87413		7. UNIT AGREEMENT NAME Rincon Unit
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface Rincon Unit 171M - 1645' FSL, 1775' FEL RINCON UNIT 117 - 1750' FSL, 990' FEL		8. FARM OR LEASE NAME Rincon Unit
14. PERMIT NO.		9. WELL NO. 171M, 117 NOTHING
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6528' GR, 6515' GR		10. FIELD AND POOL, OR WILDCAT Blanco MV, Basin DK
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec 21 T27N R6W
		12. COUNTY OR PARISH Rio Arriba
		13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	☐	WATER SHUT-OFF	☐
FRACUTURE TREAT	☐	FRACUTURE TREATMENT	☐
SHOOT OR ACIDIZE	☐	SHOOTING OR ACIDIZING	☐
REPAIR WELL	☐	(Other)	☐
PULL OR ALTER CASING	☐	REPAIRING WELL	☐
MULTIPLE COMPLETION	☐	ALTERING CASING	☐
ABANDON*	☐	ABANDONMENT*	☐
CHANGE PLANS	☐		

(Other) Install Cathodic Protection

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Proposed installation of Cathodic Protection to well casing:

PROCEDURE: Drill a 6' diameter hole, 300' deep within the existing well location boundary. Ten Dur-Iron anodes will be installed below the uppermost water bearing formation in favorable locations. This will be backfield with coke breeze (99.5% carbon) to completely surround the anodes. A 50' plug of bentonite will be installed on top of the coke breeze.

A DC rectifier will be installed on existing well location and a buried DC positive cable will be connected to the anode from the rectifier. Negative DC cables from the rectifier will also be buried and connected to well casings to be protected. These cables will be buried 18" to 24" deep (on previously disturbed ground) in existing roads and locations. See attached map.

UNOCAL's completion expectation is Jan 1, 1993.

18. I hereby certify that the foregoing is true and correct

SIGNED Mike Schell

TITLE Production Technician

DATE 7/15/92

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE _____

ACCEPTED FOR RECORD

JUL 17 1992

*See Instructions on Reverse Side

FSM

FARMINGTON RESOURCE AREA

BY DC

SIB #1

WELL NAME:

Rincon #171 m

LOCATION:

DATE: 11-16-92

TOTAL VOLUME:

14.6

TOTAL AREA:

12.2

OHMS RESISTANCE:

1.20

												ANODE READINGS			
DEPT	100 ANODE	ANODE NO.	DEPT	100 ANODE	ANODE NO.	DEPT	100 ANODE	ANODE NO.	DEPT	100 ANODE	ANODE NO.	NO.	DEPTH	NO COKE	WITH COKE
5			105	1.0		305			545			1	263	1.5	4.0
10			190	1.0		310			550			2	257	1.7	4.5
15			195	.9		315			555			3	251	1.6	4.4
20			200	1.4		300			560			4	245	1.5	3.2
25			205	1.6		305			565			5	239	1.5	2.2
30			210	1.6		390			570			6	233	1.5	3.2
35			215	1.5		395			575			7	227	1.5	3.1
40			220	1.5		400			580			8	221	1.5	3.4
45			225	1.5		405			585			9	215	1.7	3.6
50			230	1.5		410			590			10	209	1.7	3.2
55			235	1.5		415			595						
60			240	1.5		420			600						
65			245	1.7		425			605						
70			250	1.6		430			610						
75			255	1.6		435			615						
80			260	1.7		440			620						
85			265	1.2		445			625						
90			270	1.2		450			630						
95			275	.8		455			635						
100			280	.6		460			640						
105			285	.5		465			645						
110			290	.4		470			650						
115			295	1.40		475			655						
120			300			480			660						
125			305			485			665						
130			310			490			670						
135			315			495			675						
140			320			500			680						
145			325			505			685						
150	.8		330			510			690						
155	.8		335			515			695						
160	1.0		340			520			700						
165	.8		345			525			705						
170	.9		350			530			710						
175	.9		355			535			715						
180	1.0		360			540			720						

REMARKS:

Well Name Quadr 171-M Q S T R
Company Name Unocal

[illegible]

Anode Depth									
#1	#2	#3	#4	#5	#6	#7	#8	#9	#10
Anode Output (Amps)									
#1	#2	#3	#4	#5	#6	#7	#8	#9	#10
Anode Depth									
#11	#12	#13	#14	#15	#16	#17	#18	#19	#20
Anode Output (Amps)									
#11	#12	#13	#14	#15	#16	#17	#18	#19	#20
Total Circuit Resistance						No. 8 C.P. Cable Used	No. 2 C.P. Cable Used		
Volts	Amps	Ohms	Coke Breeze						

-All Construction Completed

Frank E. Burge
Signature

GROUND BED LAYOUT SKETCH

Date _____

Remarks:

Drilled to 80' land-water, drilled
water water to 300' Sunday 11-15-92

