

**DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 copies to OCD Aztec Office)**

30-039-25359

Operator: UNOCAL – Bloomfield, NM Location: Unit D Sec. 06 Twp. 26N Rng. 6W

Name of Well/Wells or Pipeline Serviced: RINCON UNIT 150E DK

Elevation: 6700 GR Completion Date: 10/03/95 Total Depth: 295' Land Type* F

Casing, Sizes, Types & Depths: NONE

If Casing is cemented, show amounts & types used: NONE

If Cement or Bentonite Plugs have been placed, show depths & amounts used: NONE

Depths & thickness of water zones with description of water when possible: NONE

Fresh, Clear, Salty, Sulfur, Etc.: NONE

Depths gas encountered: NONE

Type & amount of coke breeze used: 2500 LBS., SWB PETROLEUM COKE

Depths anodes placed: 136' 145' 155' 164' 180' 187' 193' 199' 205' 211'

Depths vent pipes placed: 0' – 300', 1" PVC

Vent pipe perforations: 1/8" PERFORATIONS FROM 100' TO 300'

Remarks: FIRST GROUND BED INSTALLED ON THIS LOCATION.

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analysis & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F–Federal; I–Indian; S–State; P–Fee
If Federal or Indian, add Lease Number.

RECEIVED
NOV - 8 1995
OIL CON. DIV.
DIST. 3

CPS GROUND BED CONSTRUCTION WORKSHEET

P/L NAME(S), NUMBER(S)	Lincoln Unit # 150 F
TOTAL VOLTS	14.8
AMPS	16.0
= OHMS	.92
DATE	11-3-95
NAME	Daryl

REMARKS (Notes for construction job)
 300' of 1" PVC 200 perforated / 2500 lb of Coke breeze

[illegible]

COMPANY Unical

DAILY DRILLING REPORT

Oct. 4th

19 95

WELL NAME:

WELL NUMBER:

SECTION:

TOWNSHIP:

RANGE:

150-E

WATER AT:

FEET:

HOLE MADE:

N/A

300'

DESCRIPTION OF FORMATION

[illegible]REMARKS: No water, no moisture.

Bruce S. Bunge

Driller

Tool Drawer

