

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 copies to OCD Aztec Office)

304M-30-039-25488

93-30-039-06539

Operator: UNOCAL – Bloomfield, NM Location: Unit P Sec. 11 Twp. 26N Rng. 7W

Name of Well/Wells or Pipeline Serviced: RINCON UNIT 304M DK/MV, RINCON UNIT 93 PC

Elevation: 6504 GR Completion Date: 10/11/95 Total Depth: 290' Land Type* F

Casing, Sizes, Types & Depths: NONE

If Casing is cemented, show amounts & types used: NONE

If Cement or Bentonite Plugs have been placed, show depths & amounts used: NONE

Depths & thickness of water zones with description of water when possible: WET AT 220'

Fresh, Clear, Salty, Sulfur, Etc.: NONE

Depths gas encountered: NONE

Type & amount of coke breeze used: 1300 LBS., SWB PETROLEUM COKE

Depths anodes placed: 195' 201' 207' 213' 219' 225' 231' 237' 243' 250'

Depths vent pipes placed: 0' – 290', 1" PVC

Vent pipe perforations: 1/8" PERFORATIONS FROM 100' TO 290'

Remarks: FIRST GROUND BED INSTALLED ON THIS LOCATION.

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analysis & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F–Federal; I–Indian; S–State; P–Fee
If Federal or Indian, add Lease Number.

RECEIVED
NOV - 8 1995
OIL CON. DIV.
DIST. 3

Cathodic Protection Services

CPS GROUND BED CONSTRUCTION WORKSHEET

CPS# 304M P/L NAME (S), NUMBER (S) Unocal - Rincon Unit 304M

WO # TOTAL VOLTS 12.1 AMPS 11.9 = OHMS 1.01 DATE 10/11/95 NAME

REMARKS (notes for construction log)

TD of the hole was at 290' - 200' 1" vent (perforated) - 100' 1" solid

1300 lbs. Loresco SW coke breeze to cover above top anode

DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #
100	.1		295			490			685					
105	.1		300			495			690					
110	.1		305			500			695					
115	.1		310			505			700					
120	.1		315			510			ANODE	DEPTH	NO	FULL		
125	.2		320			515			#	COKE	COKE	COKE		
130	.3		325			520			1	250	.6	1.9		
135	.1		330			525			2	243	.9	3.6		
140	.1		335			530			3	237	1.0	3.4		
145	.2		340			535			4	231	1.0	3.3		
150	.2		345			540			5	225	1.1	3.0		
155	.2		350			545			6	219	.8	2.7		
160	.1		355			550			7	213	.7	2.1		
165	.3		360			555			8	207	.8	1.9		
170	.1		365			560			9	201	.9	2.0		
175	.2		370			565			10	195	.7	1.8		
180	.3		375			570			11					
185	.4		380			575			12					
190	.5		385			580			13					
195	.7		390			585			14					
200	.8		395			590			15					
205	.9		400			595			16					
210	.10		405			600			17					
215	.7		410			605			18					
220	.9		415			610			19					
225	.9		420			615			20					
230	1.0		425			620			21					
235	1.1		430			625			22					
240	1.1		435			630			23					
245	1.0		440			635			24					
250	.6		445			640			25					
255	.5		450			645			26					
260	.1		455			650			27					
265	.2		460			655			28					
270	.1		465			660			29					
275	.3		470			665			30					
280	.1		475			670								
285	.3		480			675								
290	TD		485			680								

COMPANY Unocal

DAILY DRILLING REPORT

Oct 1019 95

WELL NAME:

WELL NUMBER:

SECTION:

TOWNSHIP:

RANGE:

304

WATER AT:

FEET:

HOLE MADE:

220'300

DESCRIPTION OF FORMATION

FROM

TO

FORMATION IS

COLOR

0220Sandstone220300Shale / sandstone

REMARKS:

Brian E. Burger

Driller

Tool Dresser

