

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 copies to OCD Aztec Office)

176E 30-039-25490

9- 30-039-06822

Operator: UNOCAL – Bloomfield, NM Location: Unit F Sec. 31 Twp. 27N Rng. 6W

Name of Well/Wells or Pipeline Serviced: RINCON UNIT 176E DK/MV, RINCON UNIT 9 PC

Elevation: 6625 GR Completion Date: 10/02/95 Total Depth: 300' Land Type* F

Casing, Sizes, Types & Depths: NONE

If Casing is cemented, show amounts & types used: NONE

If Cement or Bentonite Plugs have been placed, show depths & amounts used: NONE

Depths & thickness of water zones with description of water when possible: NONE

Fresh, Clear, Salty, Sulfur, Etc.: NONE

Depths gas encountered: NONE

Type & amount of coke breeze used: 2800 LBS., SWB PETROLEUM COKE

Depths anodes placed: 125' 159' 165' 170' 189' 199' 206' 213' 220' 276'

Depths vent pipes placed: 0' – 300', 1" PVC

Vent pipe perforations: 1/8" PERFORATIONS FROM 100' TO 300'

Remarks: FIRST GROUND BED INSTALLED ON THIS LOCATION.

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analysis & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F–Federal; I–Indian; S–State; P–Fee
If Federal or Indian, add Lease Number.

RECEIVED
NOV - 8 1995
OIL CON. DIV.
DIST. 3

Cathodic Protection Services

CPS GROUND BED CONSTRUCTION WORKSHEET

PS#	P/L NAME(s), NUMBER(s)					
357-00355	Rincon Unit # 176 E					
TOTAL	VOLTS	AMPS	= OHMS	DATE	NAME	
10 Anodes	14.3	11.1	1.28	10-2-95	Ann L.	

REMARKS (notes for construction log)
 300' of 1" PVC 200' perforated / 2800 lb of Coke Breeze

DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	NO COKE	FULLY COK'D
00	1.1		295	.2		490			685				
05	.9		300	1.0		495			690				
10	1.0		305			500			695				
15	1.2		310			505			700				
20	1.1		315			510			ANODE	DEPTH			
25	1.3		320			515			#				
30	1.6		325			520			1	276	6	1.2	
35	1.6		330			525			2	220	1.0	2.0	
40	1.2		335			530			3	213	1.1	2.1	
45	1.2		340			535			4	206	1.2	2.5	
50			345			540			5	199	1.3	2.3	
55	.9		350			545			6	189	1.1	2.9	
60	1.2		355			550			7	170	1.3	2.9	
65	1.3		360			555			8	165	1.3	2.8	
70	1.2		365			560			9	159	1.2	2.7	
75	.7		370			565			10	125	1.5	3.0	
80	1.6		375			570			11				
85	.9		380			575			12				
90	1.1		385			580			13				
95	1.2		390			585			14				
00	1.3		395			590			15				
05	1.3		400			595			16				
10	1.2		405			600			17				
15	.8		410			605			18				
20	1.0		415			610			19				
25	?		420			615			20				
30	2		425			620			21				
35	1.2		430			625			22				
40	1.2		435			630			23				
45	.3		440			635			24				
50	.2		445			640			25				
55	1.2		450			645			26				
60	.2		455			650			27				
65	.3		460			655			28				
70	.3		465			660			29				
75	1.6		470			665			30				
80	.4		475			670							
85	.2		480			675							
90	.1		485			680							

COMPANY Amical DAILY DRILLING REPORT Oct 1 1995

WELL NAME:	WELL NUMBER:	SECTION:	TOWNSHIP:	RANGE:
176 - E	.			Y

FEET:

300

[illegible]REMARKS: ~~REDACTED~~

Brian S. Burger Driller

Tool Breakdown

