

1640

2A- 30-045-21721

300- 30-045-26884

E

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS  
NORTHWESTERN NEW MEXICO  
(Submit 3 copies to OCD Aztec Office)

Operator MERIDAIN OIL Location: Unit NW Sec. 5 Twp 30 Rng 8

Name of Well/Wells or Pipeline Serviced HOWELL A #2A, #300

cps 1049w

Elevation 6203' Completion Date 9/28/88 Total Depth 340' Land Type\* N/A

Casing, Sizes, Types & Depths N/A

If Casing is cemented, show amounts & types used N/A

If Cement or Bentonite Plugs have been placed, show depths & amounts used  
N/A

Depths & thickness of water zones with description of water when possible:

Fresh, Clear, Salty, Sulphur, Etc. 55'

Depths gas encountered: N/a

Type & amount of coke breeze used: N/A

Depths anodes placed: 285', 275', 250', 215', 205', 195', 185', 175', 165', 155'

Depths vent pipes placed: 340'

Vent pipe perforations: BOTTOM 300'

Remarks: gb #2

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

\*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.  
If Federal or Indian, add Lease Number.

RECEIVED

MAY 31 1991

OIL CON. DIV.

DIST. 3

2A- 30-045-21721  
300- 30-045-26884

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS  
NORTHWESTERN NEW MEXICO  
(Submit 3 copies to OCD Aztec Office)

Operator MERIDIAN OIL Location: Unit NW Sec. 5 Twp 30 Rng 8

Name of Well/Wells or Pipeline Serviced HOWELL A #2A, #300

cps 1049w

Elevation 6283' Completion Date 7/26/76 Total Depth 560' Land Type\* N/A

Casing, Sizes, Types & Depths N/A

If Casing is cemented, show amounts & types used N/A

If Cement or Bentonite Plugs have been placed, show depths & amounts used

N/a

Depths & thickness of water zones with description of water when possible:

Fresh, Clear, Salty, Sulphur, Etc. 240' & 415'

RECEIVED

MAY 31 1991

Depths gas encountered: N/A

Type & amount of coke breeze used: 47 SACKS

OIL CON. DIV.

Depths anodes placed: 530', 520', 510', 500', 490', 480', 470', 440', 430', 420'

DIST. 3

Depths vent pipes placed: N/A

Vent pipe perforations: 310'

Remarks: gb #1 HOLE CAVED. ALL ANODES GOT TIGHT AT ONCE.

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included

\*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.  
If Federal or Indian, add Lease Number.