

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 Copies to OCD Aztec Office)

SS-10

4255

Operator: BLACKWOOD & NICHOLS CO. Location: Unit C, Sec. 20, Twp 30N, Rng 7W.

Name of Well/Wells or Pipeline Serviced NEBU 479R, 13A

4792 - 30-039-25315

13A - 30-039-22472

FEE

Elevation 6300' Completion Date 12-10-93 Total Depth 475' Land Type* Surface: F Mineral: SF-079060

Casing, Sizes, Types & Depths 8-5/8" SCH 40 P.V.C. - 100'

If Casing is cemented, show amounts & types used 18 sks Portland Zia I-II

If Cement or Bentonite Plugs have been placed, show depths & amounts used N/A

Depths & thickness of water zones with description of water when possible:

Fresh, Clear, Salty, Sulphur, Etc. Clear, Standing water - 260'

Depths gas encountered: N/A

Type & amount of coke breeze used: Loresco - 7000#

Depths anodes placed: 265' - 425' (15)

Depths vent pipes placed: Bottom to 4' Above Ground Level

Vent pipe perforations: Bottom - 360'


Remarks: Groundbed Located at 91' 240° from North of NEBU 479R wellhead.

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

Signed by: James K. Allen

Title: Operations Engineer Date: 2/3/94



CATHODIC GROUND BED DRILLERS REPORT

\$5-10

WELL# NEBA-479R+413A

S 20 T 30-07

[illegible]

LER Mark Briles

INSPECTOR *G. W. 21*

DRILLERS' REPORT

WELL# NEBU #479R-13A

C S 20 T 30-7

[illegible]

LER PL

INSPECTOR MDM