

30-039-07692

**OCD CATHODIC PROTECTION DEEPWELL GROUND BED REPORT
DATA SHEET: NORTHWESTERN NEW MEXICO**

SUBMIT 2 COPIES TO O.C.D. AZTEC OFFICE

OPERATOR: PHILLIPS PETROLEUM CO.
FARMINGTON, NM 87401
PHONE: 599-3400

RECEIVED
APR 24 1997

OIL CON. DIV.
DIST. 3

LOCATION INFORMATION

WELLNAME OR PIPELINE SERVED: SJ 29-6 UNIT #15 MV

ADDITIONAL WELLS: SJ 29-6 #207

LEGAL LOCATION: K 2 29 6

DATE OF INSTALLATION: 11/25/96

LEASE NUMBER: 650112

TYPE OF LEASE: FEE

PPCO RECTIFIER NUMBER: FM-179

TOTAL G/B DEPTH 380

GROUND BED INFORMATION

CASING SIZE: 8

CASING TYPE: PVC

CASING DEPTH: 20

CASING CEMENT: NO

TOP ANODE: 220

BOTTOM ANODE 360

INDIVIDUAL ANODE DEPTHS: 220,230,240,250,260,270,280,290,300,310,320,330,340,350,360

AMOUNT OF COKE: 3944

WATER INFORMATION

WATER DEPTH (1): 100

WATER DEPTH (2): N/A

CEMENT PLUGS: NO

OTHER INFORMATION

GAS DEPTH: N/A

VENT PIPE DEPTH 380

TOP OF VENT PERFORATIONS: 210

REMARKS: Sidetrack 11/96 NEW G/B DRILLED 11/96

IF ANY OF THE ABOVE DATA IS UNAVAILABLE, PLEASE INDICATE SO. COPIES OF ALL LOGS, INCLUDING DRILLERS LOGS, WATER ANALYSIS, AND WELL BORE SCHEMATICS SHOULD BE SUBMITTED WHEN AVAILABLE.
UNPLUGGED UNABANDONED WELLS ARE TO BE INCLUDED

* LAND TYPE MAY BE SHOWN. F-FEDERAL; I-INDIAN, S-STATE; P-FEE
IF FEDERAL OR INDIAN, ADD LEASE NUMBER.

Charge 1/2 to 29-6 #15
1/2 to 29-6 #207

Charge no 5304

179

CPDTGD.WK3

PHILLIPS PETROLEUM COMPANY
DEEP TYPE GROUND BED DATA

FM-

COMPANY: Phillips				DATE: 11-25-96		
WELL:				PIPELINE:		
LOCATION: 14 14 SEC.				STATE: New Mexico		
GROUNDBED: DEPTH: 380 DIAMETER: 7"				BACKFILL: Ioresco ANODES TYPE: Duriron		
DEPTH FT.	DRILLERS LOG	ANODE LOG			ANODE DEPTH	REMARKS
		I Logged	I Coked	R		
20	Shale					
30						
40						
50						
60						
70	Sandstone					
80						
90						
100		1.9				
110		1.8				
120		1.7				
130	Shale	1.3				
140		1.5				
150		1.6				
160		2.0				
170		1.7				
180		1.5				
190		1.4				
200		1.5				
210		2.0				
220		1.7	3.7	1.6	200	15
230		1.8	4.2	1.8	210	14
240	Sandstone	1.3	3.9	1.6	220	13
250		1.6	3.8	1.6	230	12
260		1.7	3.0	1.2	240	11
270		1.6	3.7	1.6	275	10
280	Shale	1.8	4.0	1.7	285	9
290		1.5	4.4	1.7	295	8
300		1.7	4.1	1.5	305	7
310		1.5	3.9	1.5	315	6
320		1.4	3.8	1.4	325	5
330		1.3	3.9	1.7	335	4
340		1.4	4.2	1.3	345	3
350		1.8	4.6	1.8	355	2

NOTES:

POWER SOURCE: Auto VOLTS: 11.67

INDICATE WATER ZONE DEPTHS 100', 240'

CASING RUN: ☒ YES / NO TYPE: PVC DEPTH: 20 CEMENTED: ☒ YES / NO

ISOLATION PLUGS SET: YES / ☒ NO IF SO, WHERE:

TOTAL: AMPS 20.4 RESISTANCE: 1.57

WELL: _____

DATE: 11-25-96

DEPTH FT.	DRILLERS LOG	ANODE LOG			ANODE DEPTH	REMARKS
		I LOGGED	I COKED	R		
360	Shale	1.9	3.8	1.3	365	1
370	✓	1.6				
380						
390						
400						
410						
420						
430						
440						
450						
460						
470						
480						
490						
500						
510						
520						
530						
540						
550						
560						
570						
580						
590						
600						
610						
620						
630						
640						
650						
660						
670						
680						
690						
700						

NOTES: _____

POWER SOURCE: _____ VOLTS: _____

INDICATE WATER ZONE DEPTHS _____

CASING RUN: YES / NO TYPE: _____ DEPTH: _____ CEMENTED: YES / NO

ISOLATION PLUGS SET: YES / NO IF SO, WHERE: _____

TOTAL: AMPS _____ RESISTANCE: _____