

30-039-07929

OCD CATHODIC PROTECTION DEEPWELL GROUND BED REPORT
DATA SHEET: NORTHWESTERN NEW MEXICO

SUBMIT 2 COPIES TO D.O.D. AZTEC OFFICE

OPERATOR: PHILLIPS PETROLEUM CO.
FARMINGTON, NM 87401
PHONE: 599-3400

RECEIVED
APR 24 1997

OIL CON. DIV.
DIST. 3

LOCATION INFORMATION

WELLNAME OR PIPELINE SERVED: SJ 31-6 UNIT #10 MV

ADDITIONAL WELLS: N/A

LEGAL LOCATION: N 32 31 6

DATE OF INSTALLATION: 11/1/96

LEASE NUMBER: 650114

TYPE OF LEASE: STATE

PPCO RECTIFIER NUMBER: FM-342

TOTAL G/B DEPTH 380

GROUND BED INFORMATION

CASING SIZE: 8

CASING TYPE: PVC

CASING DEPTH: 20

CASING CEMENT: NO

TOP ANODE: 240

BOTTOM ANODE 330

INDIVIDUAL ANODE DEPTHS: 240,250,260,270,280,290,300,310,320,330

AMOUNT OF COKE: 3506

WATER INFORMATION

WATER DEPTH (1): 200

WATER DEPTH (2): N/A

CEMENT PLUGS: NO

OTHER INFORMATION

GAS DEPTH: N/A

VENT PIPE DEPTH 380

TOP OF VENT PERFORATIONS: 230

REMARKS: NEW G/B DRILLED 11-96

IF ANY OF THE ABOVE DATA IS UNAVAILABLE, PLEASE INDICATE SO. COPIES OF ALL LOGS, INCLUDING DRILLERS LOGS, WATER ANALYSIS, AND WELL BORE SCHEMATICS SHOULD BE SUBMITTED WHEN AVAILABLE.
UNPLUGGED UNABANDONED WELLS ARE TO BE INCLUDED.

* LAND TYPE MAY BE SHOWN: F-FEDERAL; I-INDIAN; S-STATE; P-FEE
IF FEDERAL OR INDIAN, ADD LEASE NUMBER.

COMPANY: Phillips Petroleum DATE: 11-1-96
WELL: S.J. 31-6-#10 PIPELINE:
LOCATION: 14SW14 SEC. 32-31-6 STATE: N.M.
GROUNDED: DEPTH: 380' DIAMETER: 7" BACKFILL: ANODES TYPE: Duriron

DEPTH FT.	DRILLERS LOG	ANODE LOG			ANODE DEPTH	REMARKS
		I Logged	I Coked	R		
20	Sandstone					
30						
40						
50						
60						
70						
80						
90						
100						
110						
120						
130						
140						
150						
160						
170						
180						
190						
200		1.5				
210		1.1				
220		1.3				
230		1.6				
240	10 Shale, Sandy	1.0	2.8	1.1	240	
250	9	1.4	3.3	1.3	250	
260	8	1.0	3.0	1.1	260	
270	7	1.0	2.7	1.2	270	
280	6	.8	2.0	.9	280	
290	5	1.3	3.8	1.2	290	
300	4	1.4	4.3	1.3	300	
310	3	1.4	4.3	1.4	310	
320	2	1.5	3.8	1.5	320	
330	1	1.1	3.3	1.2	330	
340	Sandstone	1.0				
350		1.6				

NOTES: 2000# 10resco SW 10ke breeze

POWER SOURCE: AUTO VOLTS: 11.49
INDICATE WATER ZONE DEPTHS 200'
CASING RUN: ☒ YES ☐ NO TYPE: PVC DEPTH: 20' CEMENTED: ☒ YES ☐ NO
ISOLATION PLUGS SET: YES ☐ NO ☒ IF SO, WHERE: _____
TOTAL: AMPS 10.0 RESISTANCE: 1.14

WELL: SS 31-6 #10

DATE: 11-1-96

DEPTH FT.	DRILLERS LOG	ANODE LOG			ANODE DEPTH	REMARKS
		I LOGGED	I COKED	R		
360	Sandstone L	15				
370		3				
380						
390						
400						
410						
420						
430						
440						
450						
460						
470						
480						
490						
500						
510						
520						
530						
540						
550						
560						
570						
580						
590						
600						
610						
620						
630						
640						
650						
660						
670						
680						
690						
700						

NOTES: _____

POWER SOURCE: _____ VOLTS: _____

INDICATE WATER ZONE DEPTHS _____

CASING RUN: YES / NO TYPE: _____ DEPTH: _____ CEMENTED: YES / NO

ISOLATION PLUGS SET: YES / NO IF SO, WHERE: _____

TOTAL: AMPS _____ RESISTANCE: _____