

30-039-24580

**OCD CATHODIC PROTECTION DEEPWELL GROUND BED REPORT
DATA SHEET: NORTHWESTERN NEW MEXICO**

SUBMIT 2 COPIES TO O.C.D. AZTEC OFFICE

OPERATOR: PHILLIPS PETROLEUM CO.
FARMINGTON, NM 87401
PHONE 599-3400

RECEIVED
APR 24 1997
OIL CON. DIV.
DIST. 3

LOCATION INFORMATION

WELLNAME OR PIPELINE SERVED: SJ 29-6 UNIT #71 MV

ADDITIONAL WELLS: SJ 29-6 #209

LEGAL LOCATION: B 17 29 6

DATE OF INSTALLATION: 11/2/96

LEASE NUMBER: 650112

TYPE OF LEASE: FEDERAL

PPCO RECTIFIER NUMBER: FM-231

TOTAL G/B DEPTH 310

GROUND BED INFORMATION

CASING SIZE: 8 CASING TYPE: PVC CASING DEPTH: 20

CASING CEMENT: NO

TOP ANODE: 110 BOTTOM ANODE 290

INDIVIDUAL ANODE DEPTHS: 110,120,130,140,150,160,170,180,190,200,240,250,260,280,290

AMOUNT OF COKE: 3500

WATER INFORMATION

WATER DEPTH (1): 205 WATER DEPTH (2):

CEMENT PLUGS: N/A

OTHER INFORMATION

GAS DEPTH: N/A

VENT PIPE DEPTH 310 TOP OF VENT PERFORATIONS: 100

REMARKS: NEW G/B DRILLED 11-96

IF ANY OF THE ABOVE DATA IS UNAVAILABLE, PLEASE INDICATE SO. COPIES OF ALL LOGS, INCLUDING DRILLERS LOGS, WATER ANALYSIS, AND WELL BORE SCHEMATICS SHOULD BE SUBMITTED WHEN AVAILABLE.
UNPLUGGED UNABANDONED WELLS ARE TO BE INCLUDED

* LAND TYPE MAY BE SHOWN F-FEDERAL, I-INDIAN, S-STATE, P-FEE
IF FEDERAL OR INDIAN, ADD LEASE NUMBER

COMPANY: Phillips Petroleum		DATE: 11-2-96				
WELL: 55-29-6 #71 + #209		PIPELINE:				
LOCATION: 14 NE 14 SEC. 17-29-6		STATE: N. M.				
GROUNDBED: DEPTH: 310 DIAMETER: 7"		BACKFILL: ANODES TYPE: Duriron				
DEPTH FT.	DRILLERS LOG	ANODE LOG			ANODE DEPTH	REMARKS
		I Logged	I Coked	R		
20	Sandstone					
30						
40						
50						
60						
70						
80	Shale					
90						
100	Sandstone	1.1				
110	Shale	15	1.6	4.8	1.7	110
120		14	2.9	6.8	3.2	120
130		13	3.0	7.4	3.2	130
140		12	3.1	7.4	3.4	140
150		11	1.7	5.4	2.1	150
160		10	1.1	3.8	1.3	160
170		9	1.5	4.3	1.7	170
180		8	2.5	5.4	2.7	180
190		7	2.0	4.8	2.1	190
200		6	1.2	3.7	1.3	200
210	Sandstone	1.6				
220		1.7				
230		1.8				
240	Shale	5	1.5	3.3	1.5	240
250		4	1.8	3.9	2.0	250
260		3	1.2	2.9	1.2	260
270	Sandstone	1.5				
280	Shale	2	1.3	2.9	1.6	280
290		1	1.9	3.4	1.8	290
300		1.5				
310	Sandstone					
320						
330						
340						
350						

NOTES: 2700# 101PSC SW ckt breeze

POWER SOURCE: Auto VOLTS: 10.87

INDICATE WATER ZONE DEPTHS 30', 60', 205', 270'

CASING RUN: YES / NO TYPE: PVC 8" DEPTH: 20' CEMENTED: YES / NO

ISOLATION PLUGS SET: YES / NO IF SO, WHERE:

TOTAL: AMPS 20.6 RESISTANCE: .52