

30-045-10562

**OCD CATHODIC PROTECTION DEEPWELL GROUNDBED REPORT
DATA SHEET: NORTHWESTERN NEW MEXICO**

SUBMIT 2 COPIES TO O.C.D. AZTEC OFFICE

OPERATOR: PHILLIPS PETROLEUM CO.
FARMINGTON, NM 87401
PHONE: 589-3400

RECEIVED
APR 24 1997

OIL CON. DIV.
DIST. 3

LOCATION INFORMATION

WELLNAME OR PIPELINE SERVED: SJ 32-8 UNIT #10 MV

ADDITIONAL WELLS: N/A

LEGAL LOCATION: H 24 31 8

DATE OF INSTALLATION: 11/26/96

LEASE NUMBER: 650117

TYPE OF LEASE: FEDERAL

PPCO RECTIFIER NUMBER: FM-446

TOTAL G/B DEPTH 300

GROUNDBED INFORMATION

CASING SIZE: 8 CASING TYPE: PVC CASING DEPTH: 20

CASING CEMENT: NO

TOP ANODE: 140 BOTTOM ANODE 280

INDIVIDUAL ANODE DEPTHS: 140,150,160,170,180,190,200,210,270,280

AMOUNT OF COKE: 3944

WATER INFORMATION

WATER DEPTH (1): 250 WATER DEPTH (2): N/A

CEMENT PLUGS: NO

OTHER INFORMATION

GAS DEPTH: N/A

VENT PIPE DEPTH 300 TOP OF VENT PERFORATIONS: 130

REMARKS: Sidetrack 11/96 NEW G/B DRILLED 11-96

IF ANY OF THE ABOVE DATA IS UNAVAILABLE, PLEASE INDICATE SO. COPIES OF ALL LOGS, INCLUDING DRILLERS LOGS, WATER ANALYSIS, AND WELL BORE SCHEMATICS SHOULD BE SUBMITTED WHEN AVAILABLE.
UNPLUGGED UNABANDONED WELLS ARE TO BE INCLUDED.

* LAND TYPE MAY BE SHOWN: F-FEDERAL; I-INDIAN; S-STATE; P-FEE
IF FEDERAL OR INDIAN, ADD LEASE NUMBER.

Change to 32-8 #10 change no. 405306

CPDTGD.WK3

PHILLIPS PETROLEUM COMPANY
DEEP TYPE GROUND BED DATA

FM-

446

COMPANY: <u>Phillips</u>				DATE: <u>11-26-96</u>		
WELL:				PIPELINE:		
LOCATION: <u>14</u> <u>14</u> SEC.				STATE: <u>New Mexico</u>		
GROUNDBED: DEPTH: <u>300</u> DIAMETER: <u>7"</u>				BACKFILL: <u>loess</u> ANODES TYPE: <u>Duriron</u>		
DEPTH FT.	DRILLERS LOG	ANODE LOG			ANODE DEPTH	REMARKS
		I Logged	I Coked	R		
20	Shale					
30						
40						
50						
60						
70						
80	Sandstone					
90						
100		1.2				
110		1.2				
120		1.6				
130		1.8				
140	Shale	1.7	4.2	1.7	135	10
150		1.5	4.3	1.4	145	9
160		2.1	4.9	2.2	155	8
170		2.0	5.0	2.0	165	7
180		2.2	5.7	2.4	175	6
190		2.3	5.7	2.5	185	5
200		1.6	4.9	1.7	195	4
210		1.5	4.4	1.7	205	3
220	Sandstone	1.4				
230		1.5				
240		1.5				
250		0.9				
260		1.7				
270	Shale	1.4	3.3	1.7	270	2
280		1.3	3.0	1.3	280	1
290	Sandstone	1.2				
300		1.1				
310						
320						
330						
340						
350						

NOTES: H2O AT 250' (1 gpm)

POWER SOURCE: AUTO VOLTS: 11.60

INDICATE WATER ZONE DEPTHS 250'

CASING RUN: ☒ YES / NO TYPE: PVC DEPTH: 20 CEMENTED: ☒ YES / NO

ISOLATION PLUGS SET: YES / ☒ NO IF SO, WHERE: _____

TOTAL: AMPS 15.0 RESISTANCE: 1.77