

1556

2- 30-045-08806

7- 30-045-25338

210- 30-045-27121

E

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS.
NORTHWESTERN NEW MEXICO

(Submit 3 copies to OCD Aztec Office)

Operator MERIDIAN OIL INC. Location: Unit NE Sec. 5 Twp 29 Rng 8Name of Well/Wells or Pipeline Serviced SUNRAY #2, #7, #210

cps 2104w

Elevation 6270' Completion Date 6/18/64 Total Depth 560' Land Type* N/ACasing, Sizes, Types & Depths N/AIf Casing is cemented, show amounts & types used N/A

If Cement or Bentonite Plugs have been placed, show depths & amounts used

N/A

Depths & thickness of water zones with description of water when possible:

Fresh, Clear, Salty, Sulphur, Etc. N/ADepths gas encountered: N/AType & amount of coke breeze used: 6900 lbs.Depths anodes placed: 500', 494', 488', 482', 476', 470'Depths vent pipes placed: N/AVent pipe perforations: N/ARemarks: gb #2 : HOLE CAVED TO 511.**RECEIVED**
MAY 31 1991,
OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

CATHODIC PROTECTION CONSTRUCTION REPORT

DAILY LOG

Date 6-18-64

Well Name <u>SUNRAY No. 2</u>			CPS No. <u>264W 2104W</u>			
Location <u>NE 5-29-8</u>			Work Order No. <u>52275</u>			
Anode Hole Depth <u>560</u>	Total Drilling Rig Time <u>44 1/2 Hrs</u>	Type & Size Bit Used <u>6 1/4 - 9255X = 120, 8243 = 245</u>		No. Sacks Mud Used <u>36</u>		
No. Sacks Lost Circulation Mat'l Used <u>0</u>	Anode Depth					
	#1 <u>500</u>	#2 <u>494</u>	#3 <u>488</u>	#4 <u>482</u>	#5 <u>476</u>	#6 <u>470</u>
Total Lbs. Coke Used <u>465 kgs = 6900</u>	Anode Output (Volts)					
	#1 <u>3.0</u>	#2 <u>3.2</u>	#3 <u>3.2</u>	#4 <u>4.2</u>	#5 <u>4.2</u>	#6 <u>3.7</u>
Total Circuit Resistance	Volts <u>11.7</u>		Amps <u>8.6</u>		Ohms <u>1.36</u>	
			No. Ft. Surface Cable Conduit <u>185</u>			

Drilling Log (Attach Hereto). ☐

Remarks: Hole Drilled to 560; Cased to 511.

All Construction Completed

Forrester

(Signature)

GROUND BED LAYOUT SKETCH



