

#500 30-045-28932

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Inc. Location: Unit A Sec. 28 Twp 27 Rng 10

Name of Well/Wells or Pipeline Serviced _____

MC ADAMS #500

Elevation _____ Completion Date _____ Total Depth _____ Land Type F

Casing Strings, Sizes, Types & Depths 8 1/2" Set 58' of 8" PVC Casing.

NO GAS, WATER, OR BOULDERS WERE ENCOUNTERED DURING CASING.

If Casing Strings are cemented, show amounts & types used Cemented

WITH 14 SACKS.

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NO

Depths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. FRESH WATER 100'

Depths gas encountered: NO

Ground bed depth with type & amount of coke breeze used: 362' deep

with 5300 lbs Ashbury 2 1/8" R Flo Coke

Depths anodes placed: 310, 300, 290, 278, 269, 260, 251, 242, 233, 224, 200, 191, 182, 173, 115

Depths vent pipes placed: 362'

Vent pipe perforations: bottom 280

Remarks: _____

RECEIVED

JAN 31 1994

OIL CON. DIV.

DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.

If Federal or Indian, add Lease Number.