

#500 30-045-28978

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Inc. Location: Unit K Sec. 07 Twp 27 Rng 10

Name of Well/Wells or Pipeline Serviced _____

Rowley #500

Elevation _____ Completion Date _____ Total Depth _____ Land Type F

Casing Strings, Sizes, Types & Depths Set 600 of 8" PVC Casing

If Casing Strings are cemented, show amounts & types used Cemented

WITH 16 SACKS.

If Cement or Bentonite Plugs have been placed, show depths & amounts used

Yes Installed 54' cement plug

Depths & thickness of water zones with description of water: Fresh, Clear,

Salty, Sulphur, Etc. HIT FRESH WATER AT 15' DURING CASING. WATER AT 100'

CAUGHT sample

Depths gas encountered: No

Ground bed depth with type & amount of coke breeze used: 392' with

5500 lbs. of Asbury 218 R Flo Coke

Depths anodes placed: 372, 360, 340, 329, 320, 310, 223, 214, 206, 197, 188, 178, 168, 158, 148

Depths vent pipes placed: 392'

Vent pipe perforations: bottom 300'

Remarks: _____

RECEIVED

JAN 31 1994

OIL CON.

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.