

30-045-27023

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS  
NORTHWESTERN NEW MEXICO  
(Submit 3 copies to OCD Aztec Office)

Operator MERIDIAN OIL Location: Unit A Sec. 28 Twp 30 Rng 9

Name of Well/Wells or Pipeline Serviced TURNER #251

cps 3w

Elevation 5836 Completion Date 7/20/90 Total Depth 300' Land Type\* N/A

Casing, Sizes, Types & Depths N/A

If Casing is cemented, show amounts & types used N/A

If Cement or Bentonite Plugs have been placed, show depths & amounts used  
N/A

Depths & thickness of water zones with description of water when possible:  
Fresh, Clear, Salty, Sulphur, Etc. WATER AT 280' to 300'. CEMENTED BOTTOM 30' OF  
HOLE TO SEAL OFF WATER. SAMPLE TAKEN.

Depths gas encountered: N/A

Type & amount of coke breeze used: 270' WITH 3300 lbs. ASHBURY PETROLEUM COKE.

Depths anodes placed: 235', 225', 215', 205', 195', 185', 175', 165', 155', 145'

Depths vent pipes placed: 250' 1" VENT PIPE

Vent pipe perforations: 150'

Remarks: gb #3

RECEIVED

MAY 31 1991

OIL COM

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

\*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.  
If Federal or Indian, add Lease Number.