

30045-10250

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 copies to OCD Aztec Office)

Operator MERIDIAN OIL Location: Unit SW Sec. 28 Twp 31 Rng 8

Name of Well/Wells or Pipeline Serviced HOWELL D #1

cps 247w

Elevation 6483' Completion Date 6/20/74 Total Depth 700' Land Type* N/A

Casing, Sizes, Types & Depths N/A

If Casing is cemented, show amounts & types used N/A

If Cement or Bentonite Plugs have been placed, show depths & amounts used
N/A

Depths & thickness of water zones with description of water when possible:
Fresh, Clear, Salty, Sulphur, Etc. 460'

RECEIVED

MAY 31 1991

Depths gas encountered: N/A

**OIL CON. D¹
DIST. ?**

Type & amount of coke breeze used: 12700 lbs.

Depths anodes placed: 660', 650', 640', 630', 620', 495', 485', 475', 465', 455'

Depths vent pipes placed: N/A

Vent pipe perforations: 495'

Remarks: qb #3 FIRST HOLE CAVED AT 430'. LOST LOGGING ANODE AT 600'.

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

30-045-10250

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

(Submit 3 copies to OCD Aztec Office)

Operator MERIDIAN OIL Location: Unit SW Sec. 28 Twp 31 Rng *

Name of Well/Wells or Pipeline Serviced HOWELL D #1

cps 247w

Elevation 6483' Completion Date 10/14/69 Total Depth 720' Land Type* N/A

Casing, Sizes, Types & Depths N/A

If Casing is cemented, show amounts & types used N/A

If Cement or Bentonite Plugs have been placed, show depths & amounts used

N/A

Depths & thickness of water zones with description of water when possible:

Fresh, Clear, Salty, Sulphur, Etc. WET SPOTS-120', 180', 275', 300'

Depths gas encountered: N/A

Type & amount of coke breeze used: 103 SACKS

Depths anodes placed: 668', 662', 656', 650', 644', 638', 632', 626', 460'

Depths vent pipes placed: 662' OF 3/4" HOSE

Vent pipe perforations: 500'

Remarks: gb #2 EPOXY POURED ABOVE SHRINK SLEEVE

RECEIVED

MAY 31 1991

OIL CON. DIV

DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

30-045-10250

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 copies to OCD Aztec Office)

Operator MERIDIAN OIL Location: Unit SW Sec. 28 Twp 31 Rng 8

Name of Well/Wells or Pipeline Serviced HOWELL D #1

cps 247w

Elevation 6483' Completion Date 5/10/63 Total Depth 180' Land Type* N/A

Casing, Sizes, Types & Depths N/A

If Casing is cemented, show amounts & types used N/A

If Cement or Bentonite Plugs have been placed, show depths & amounts used
N/A

Depths & thickness of water zones with description of water when possible:
Fresh, Clear, Salty, Sulphur, Etc. N/A

Depths gas encountered: N/A

Type & amount of coke breeze used: 1360 lbs.

Depths anodes placed: 110', 104', 90', 84', 78', 40'

Depths vent pipes placed: N/A

Vent pipe perforations: N/A

Remarks: qb #1

RECEIVED
MAY 31 1991
OIL CON. DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.